

Thresholded Covering Algorithms for Robust and Max-Min Optimization*

Anupam Gupta[†]

Viswanath Nagarajan[‡]

R. Ravi[§]

Abstract

The general problem of robust optimization is this: one of several possible scenarios will appear tomorrow and require to be covered, but things are more expensive tomorrow than they are today. What should you anticipatorily buy today, so that the worst-case cost (summed over both days) is minimized? We consider the k -robust model where the possible outcomes tomorrow are given by all demand-subsets of size k .

In this paper, we give the following simple and intuitive template for k -robust problems: *having built some anticipatory solution, if there exists a single demand whose augmentation cost is larger than some threshold (which is $\approx \text{Opt}/k$), augment the anticipatory solution to cover this demand as well, and repeat.* We show that this template gives improved approximation algorithms for k -robust Steiner tree and set cover, and present the first approximation algorithms for k -robust Steiner forest, minimum-cut and multicut. Our main technical contribution lies in proving certain net-type properties for these covering problems, which are based on dual-rounding and primal-dual ideas; these properties might be of some independent interest. All the approximation ratios (except for multicut) are nearly optimal.

As a by-product of our techniques, we get algorithms for max-min problems of the form: “*given a covering problem instance, which k of the elements are costliest to cover?*” If the covering problem does not naturally define a submodular function, very little is known about these problems. For the problems mentioned above, we show that their k -max-min versions have performance guarantees similar to those for the k -robust problems.

1 Introduction

Consider the following k -robust set cover problem: we are given a set system $(U, \mathcal{F} \subseteq 2^U)$. Tomorrow some set of k elements $S \subseteq U$ will want to be covered; however, today we don’t know what this set will be. One strategy is to wait until tomorrow and buy an $O(\log n)$ -approximate set cover for this set. However, sets are cheaper today: they will cost λ times as much tomorrow as they cost today. Hence, it may make sense to buy some anticipatory partial solution today (i.e. in the first-stage), and then complete it tomorrow (i.e. second-stage) once we know the actual members of the set S . Since we do not know anything about the set S (or maybe we are risk-averse), we want to plan for the worst-case, and minimize:

$$(\text{cost of anticipatory solution}) + \lambda \cdot \max_{S: |S| \leq k} (\text{additional cost to cover } S).$$

Early approximation results for robust problems [11, 20] had assumed that the collection of possible sets S was explicitly given (and the performance guarantee depended logarithmically on the size of this collection). Since this seemed quite restrictive, Feige et al. [14] proposed the k -robust model where any of the $\binom{n}{k}$ subsets S of size k

*An extended abstract containing the results of this paper and of [23] appeared jointly in *Proceedings of the 37th International Colloquium on Automata, Languages and Programming (ICALP)*, 2010.

[†]Computer Science Department, Carnegie Mellon University, Pittsburgh, PA 15213, USA. Supported in part by NSF awards CCF-0448095 and CCF-0729022, and an Alfred P. Sloan Fellowship. Email: anupamg@cs.cmu.edu

[‡]IBM T.J. Watson Research Center, Yorktown Heights, NY 10598, USA. Email: viswanath@us.ibm.com

[§]Tepper School of Business, Carnegie Mellon University, Pittsburgh, PA 15213, USA. Supported in part by NSF grant CCF-0728841. Email: ravi@cmu.edu

could arrive. Though this collection of possible sets was potentially exponential sized (for large values of k), the hope was to get results that did not depend polynomially on k .

For the k -robust set cover problem, Feige et al. [14] gave an $O(\log m \log n)$ -approximation algorithm using the online algorithm for set cover within an LP-rounding-based algorithm (à la [33]). They also showed k -robust set cover to be $\Omega(\frac{\log m}{\log \log m} + \log n)$ hard—which left a logarithmic gap between the upper and lower bounds. However, an online algorithm based approach is unlikely to close this gap, since the online algorithm for set cover is necessarily a log-factor worse than its offline counterparts [3].

Closely related to the k -robust model are k -max-min problems, where given a covering problem instance the goal is to determine the k -set of demands that are costliest to cover. Indeed, [14] used k -max-min set cover as a subroutine in their algorithm for k -robust set cover. If the covering problem defines a submodular objective then the k -max-min problem can be solved via constrained submodular optimization. However, most natural covering problems do not yield submodular functions, and so previous results cannot be applied directly. For k -max-min set cover [14] used an online algorithm to obtain an $O(\log m \log n)$ -approximation algorithm.

Apart from improving these results in context of set cover, one may want to develop algorithms for other k -robust and k -max-min problems. E.g., for the k -robust min-cut problem, some set S of k sources will want to be separated from the sink vertex tomorrow, and we want to find the best way to cut edges to minimize the total cost incurred (over the two days) for the worst-case k -set S . Similarly, in the k -max-min Steiner forest, we are given a metric space with a collection of source-sink pairs, and seek k source-sink pairs that incur the maximum (Steiner forest) connection cost. Although the online-based-framework [14] can be extended to give algorithms for other k -max-min problems, it does not yield approximation guarantees better than the (deterministic) online competitive ratios. Moreover, for k -robust problems other than set cover, the LP-rounding framework in [14] does not extend directly; this obstacle was also observed by Khandekar et al. [27] who studied k -robust Steiner tree and facility location.

1.1 Main Results

In this paper, we present a general template to design algorithms for k -robust and k -max-min problems. We go beyond the online-based approach and obtain tighter approximation ratios that nearly match the offline guarantees; see the table below. We improve on previous results, by obtaining an $O(\log m + \log n)$ factor for k -robust set cover, and improving the constant in the approximation factor for Steiner tree. We also give the first algorithms for some other standard covering problems, getting constant-factor approximations for both k -robust Steiner forest—which was left open by Khandekar et al.—and for k -robust min-cut, and an $O(\frac{\log^2 n}{\log \log n})$ approximation for k -robust multicut. Our algorithms do not use a max-min subroutine directly: however, our approach ends up giving us approximation algorithms for k -max-min versions of set cover, Steiner forest, min-cut and multicut; all but the one for multicut are best possible under standard assumptions.

An important contribution of our work is the simplicity of the algorithms, and the ideas in their analysis. The following is our actual algorithm for k -robust set cover.

Suppose we “guess” that the maximum second-stage cost in the optimal solution is T . Let $A \subseteq U$ be all elements for which the cheapest set covering them costs more than $\beta \cdot T/k$, where $\beta = O(\log m + \log n)$. We build a set cover on A as our first stage. (Say this cover costs C_T .)

To remove the guessing, try all values of T and choose the solution that incurs the least total cost $C_T + \lambda \beta T$. Clearly, by design, no matter which k elements arrive tomorrow, it will not cost us more than $\lambda \cdot k \cdot \beta T/k = \lambda \beta T$ to cover them, which is within β of what the optimal solution pays. This guess-and-verify framework is formalized in Sections 2.1 and 2.2.

The key step of our analysis is to argue why C_T is close to optimum. We briefly describe the intuition; details appear in Section 3. Suppose $C_T \gg \beta \text{Opt}$: then the fractional solution to the LP for set cover for A would cost $\gg \frac{\beta}{\ln n} \text{Opt} \geq \text{Opt}$, and so would its dual. Our key technical contribution is to show how to “round” this dual LP to find a “witness” $A' \subseteq A$ with only k elements, and also a corresponding feasible dual of value $\gg \text{Opt}$ —i.e.,

the dual value does not decrease much in the rounding. This step uses the fact that each element in A is expensive to cover individually. Using duality again, this proves that the optimal LP value, and hence the optimal set cover for these k elements A' , would cost much more than Opt —a contradiction!

In fact, our algorithms for the other k -robust problems are almost identical to this one; indeed, the only slightly involved algorithm is that for k -robust Steiner forest. Of course, the proofs to bound the cost C_T need different ideas in each case. These involve establishing certain *net-type properties* for the respective covering problems (which imply the existence of such a witness $A' \subseteq A$ of size k), and represent our main technical contribution. The proofs for set cover, min-cut and multicut are based on *dual-rounding*. In the case of Steiner forest, directly rounding the dual is difficult, and we give a *primal-dual* argument.

For the cut-problems, one has to deal with additional issues because Opt consists of two stages that have to be charged to separately, and this requires a careful Gomory-Hu-tree-based charging. Even after this, we have to show the following net-type property: if the cut for a set of sources A is large (costs $\gg \text{Opt}$) and each source in A has a high individual cut ($\gg \text{Opt}/k$) then there is a witness $A' \subseteq A$ of at most k sources for which the cut is also large ($\gg \text{Opt}$). To this end, we prove new flow-aggregation lemmas for single-sink flows using Steiner-tree-packing results, and for multiflows using oblivious routing [30]; both proofs are possibly of independent interest.

To get a quick overview of our basic approach, see the analysis for Steiner tree in Appendix A. While the result is simple and does not require rounding the dual, it is a nice example of our framework in action. In Section 2 we present the formal framework for k -robust and k -max-min problems, and abstract out the properties that we'd like from our algorithms. Then Section 3 contains such an algorithm for k -robust set cover—Min-cut, Steiner forest and multicut appear in Sections 4, 6 and 5. The table below summarizes the best-known approximation ratios for various covering problems in the offline, k -robust and online models (results denoted $*$ are in the present paper).

Problem	Offline	k -robust	Deterministic Online
Set Cover	$\ln n$ $(1 - o(1)) \ln n$ [13]	$O(\log m + \log n)$ (*) $\Omega\left(\log n + \frac{\log m}{\log \log m}\right)$ [14]	$O(\log m \cdot \log n)$ [3] $\Omega\left(\frac{\log m \cdot \log n}{\log \log m + \log \log n}\right)$ [3]
Steiner Tree	1.39 [6]	4.5 (*)	$\Theta(\log n)$ [25]
Steiner Forest	2 [1, 19]	10 (*)	$\Theta(\log n)$ [5]
Minimum Cut	1	17 (*)	$O(\log^3 n \cdot \log \log n)$ [4, 24]
Multicut	$O(\log n)$ [18]	$O\left(\frac{\log^2 n}{\log \log n}\right)$ (*)	$O(\log^3 n \cdot \log \log n)$ [4, 24]

1.2 Related Work

Approximation algorithms for robust optimization was initiated by Dhamdhere et al. [11]: they study the case when the scenarios were explicitly listed, and gave constant-factor approximations for Steiner tree and facility location, and logarithmic approximations to mincut/multicut problems. Golovin et al. [20] improved the mincut result to a constant factor approximation, and also gave an $O(1)$ -approximation for robust shortest-paths. The algorithms in [20] were also “thresholded algorithms” and the algorithms in this paper can be seen as natural extensions of that idea to more complex uncertainty sets and larger class of problems (the uncertainty set in [20] only contained singleton demands).

The k -robust model was introduced in Feige et al. [14], where they gave an $O(\log m \log n)$ -approximation for set cover; here m and n are the number of sets and elements in the set system. To get such an algorithm [14] first gave an $O(\log m \log n)$ -approximation algorithm for k -max-min set-cover problem using the online algorithm for set cover [3]. They then used the k -max-min problem as a separation oracle in an LP-rounding-based algorithm (à la [33]) to get the same approximation guarantee for the k -robust problem. They also showed an $\Omega(\frac{\log m}{\log \log m})$ hardness of approximation for k -max-min and k -robust set cover. Khandekar et al. [27] noted that the LP-based techniques of [14] did not give good results for Steiner tree, and developed new combinatorial constant-factor approximations for k -robust versions of Steiner tree, Steiner forest on trees and facility location. Using our framework, the algorithm we get for Steiner tree can be viewed as a rephrasing of their algorithm—our proof is arguably

more transparent and results in a better bound. Our approach can also be used to get a slightly better ratio than [27] for the Steiner forest problem on trees.

Constrained submodular maximization problems [29, 15, 35, 7, 37] appear very relevant at first sight: e.g., the k -max-min version of min-cut (“find the k sources whose separation from the sink costs the most”) is precisely submodular maximization under a cardinality constraint, and hence is approximable to within $(1 - 1/e)$. But apart from min-cut, the other problems do not give us submodular functions to maximize, and massaging the functions to make them submodular seems to lose logarithmic factors. E.g., one can use tree embeddings [12] to reduce Steiner tree to a problem on trees and make it submodular. In other cases, one can use online algorithms to get submodular-like properties and obtain approximation algorithms for the k -max-min problems (as in [14]). Though the LP-based framework [14] for k -robust problems does not seem to extend to problems other than set cover, in the companion paper [23] we give a general algorithm for k -robust covering using offline and online algorithms. However, since our goal in this paper is to obtain approximation factors better than the online competitive ratios, it is unclear how to use these results.

Considering the *average* instead of the worst-case performance gives rise to the well-studied model of stochastic optimization [31, 26]. Some common generalizations of the robust and stochastic models have been considered (see, e.g., Swamy [36] and Agrawal et al. [2]).

To the best of our knowledge, none of the k -max-min problems other than min-cut and set cover [14] have been studied earlier. The k -*min-min* versions of covering problems (i.e. “which k demands are the *cheapest* to cover?”) have been extensively studied for set cover [34, 16], Steiner tree [17], Steiner forest [22], min-cut and multicut [21, 30]. However these problems seem to be related to the k -max-min versions only in spirit.

2 Notation and Definitions

Deterministic covering problems. A covering problem Π has a ground-set E of elements with costs $c : E \rightarrow \mathbb{R}_+$, and n covering requirements (often called demands or clients), where the solutions to the i -th requirement is specified—possibly implicitly—by a family $\mathcal{R}_i \subseteq 2^E$ which is upwards closed (since this is a covering problem). Requirement i is *satisfied* by solution $S \subseteq E$ iff $S \in \mathcal{R}_i$. The covering problem $\Pi = \langle E, c, \{\mathcal{R}_i\}_{i=1}^n \rangle$ involves computing a solution $S \subseteq E$ satisfying all n requirements and having minimum cost $\sum_{e \in S} c_e$. E.g., in set cover, “requirements” are items to be covered, and “elements” are sets to cover them with. In Steiner tree, requirements are terminals to connect to the root and elements are the edges; in multicut, requirements are terminal pairs to be separated, and elements are edges to be cut.

Robust covering problems. This problem, denoted $\text{Robust}(\Pi)$, is a *two-stage optimization* problem, where elements are possibly bought in the first stage (at the given cost) or the second stage (at cost λ times higher). In the second stage, some subset $\omega \subseteq [n]$ of requirements (also called a *scenario*) materializes, and the elements bought in both stages must satisfy each requirement in ω . Formally, the input to problem $\text{Robust}(\Pi)$ consists of (a) the covering problem $\Pi = \langle E, c, \{\mathcal{R}_i\}_{i=1}^n \rangle$ as above, (b) a set $\Omega \subseteq 2^{[n]}$ of scenarios (possibly implicitly given), and (c) an inflation parameter $\lambda \geq 1$. A feasible solution to $\text{Robust}(\Pi)$ is a set of *first stage elements* $E_0 \subseteq E$ (bought without knowledge of the scenario), along with an *augmentation algorithm* that given any $\omega \in \Omega$ outputs $E_\omega \subseteq E$ such that $E_0 \cup E_\omega$ satisfies all requirements in ω . The objective function is to minimize: $c(E_0) + \lambda \cdot \max_{\omega \in \Omega} c(E_\omega)$. Given such a solution, $c(E_0)$ is called the first-stage cost and $\max_{\omega \in \Omega} c(E_\omega)$ is the second-stage cost.

k -robust problems. In this paper, we deal with robust covering problems under *cardinality* uncertainty sets: i.e., $\Omega := \binom{[n]}{k} = \{S \subseteq [n] \mid |S| = k\}$. We denote this problem by $\text{Robust}_k(\Pi)$.

Max-min problems. Given a covering problem Π and a set Ω of scenarios, the *max-min* problem involves finding a scenario $\omega \in \Omega$ for which the cost of the min-cost solution to ω is maximized. Note that by setting $\lambda = 1$ in any robust covering problem, *the optimal value of the robust problem equals that of its corresponding max-min problem*. In a **k -max-min problem** we have $\Omega = \binom{[n]}{k}$.

2.1 The Abstract Properties we want from our Algorithms

Our algorithms for robust and max-min versions of covering problems are based on the following guarantee.

Definition 2.1 *An algorithm is $(\alpha_1, \alpha_2, \beta)$ -discriminating iff given as input any instance of $\text{Robust}_k(\Pi)$ and a threshold T , the algorithm outputs (i) a set $\Phi_T \subseteq E$, and (ii) an algorithm $\text{Augment}_T : \binom{[n]}{k} \rightarrow 2^E$, such that:*

- A. *For every scenario $D \in \binom{[n]}{k}$,*
 - (i) *the elements in $\Phi_T \cup \text{Augment}_T(D)$ satisfy all requirements in D , and*
 - (ii) *the resulting augmentation cost $c(\text{Augment}_T(D)) \leq \beta \cdot T$.*
- B. *Let Φ^* and T^* (respectively) denote the first-stage and second-stage cost of an optimal solution to the $\text{Robust}_k(\Pi)$ instance. If the threshold $T \geq T^*$ then the first stage cost $c(\Phi_T) \leq \alpha_1 \cdot \Phi^* + \alpha_2 \cdot T^*$.*

The next lemma shows why having a discriminating algorithm is sufficient to solve the robust problem. The issue to address is that having guessed T for the optimal second stage cost, we have no direct way of verifying the correctness of that guess—hence we choose the best among all possible values of T . For $T \approx T^*$ the guarantees in Definition 2.1 ensure that we pay $\approx \Phi^* + T^*$ in the first stage, and $\approx \lambda T^*$ in the second stage; for guesses $T \ll T^*$, the first-stage cost in guarantee (2) is likely to be large compared to Opt.

Lemma 2.2 *If there is an $(\alpha_1, \alpha_2, \beta)$ -discriminating algorithm for a robust covering problem $\text{Robust}_k(\Pi)$, then for every $\epsilon > 0$ there is a $((1 + \epsilon) \cdot \max \{ \alpha_1, \beta + \frac{\alpha_2}{\lambda} \})$ -approximation algorithm for $\text{Robust}_k(\Pi)$.*

Proof: Let $\mathcal{A}$ denote an algorithm for $\text{Robust}_k(\Pi)$ such that it is $(\alpha_1, \alpha_2, \beta)$ -discriminating. Let ground-set $E = [m]$, and $c_{\max} := \max_{e \in [m]} c_e$. By scaling, we may assume WLOG that all costs in the $\text{Robust}_k(\Pi)$ instance are integral. Let $\epsilon > 0$ be any value as given by the lemma (where $\frac{1}{\epsilon}$ is polynomially bounded), and $N := \lceil \log_{1+\epsilon} (m c_{\max}) \rceil + 1$; note that N is polynomial in the input size. Define $\mathcal{T} := \{ (1 + \epsilon)^i \mid 0 \leq i \leq N \}$.

The approximation algorithm for $\text{Robust}_k(\Pi)$ runs the $(\alpha_1, \alpha_2, \beta)$ -discriminating algorithm $\mathcal{A}$ for every choice of $T \in \mathcal{T}$ (here $|\mathcal{T}|$ is polynomially bounded), and returns the solution corresponding to:

$$\tilde{T} := \arg \min \{ c(\Phi_T) + \lambda \cdot \beta T \mid T \in \mathcal{T} \}.$$

Recall that T^* denotes the optimal second-stage cost, clearly $T^* \leq m \cdot c_{\max}$. Let $i^* \in \mathbb{Z}_+$ be chosen such that $(1 + \epsilon)^{i^*-1} < T^* \leq (1 + \epsilon)^{i^*}$; also let $T' := (1 + \epsilon)^{i^*}$ (note that $T' \in \mathcal{T}$). The objective value of the solution from $\mathcal{A}$ for threshold $\tilde{T}$ can be bounded as follows.

$$\begin{aligned} c(\Phi_{\tilde{T}}) + \lambda \cdot \max_{\omega \in \Omega} c(\text{Augment}_{\tilde{T}}(\omega)) &\leq c(\Phi_{\tilde{T}}) + \lambda \cdot \beta \tilde{T} \\ &\leq c(\Phi_{T'}) + \lambda \cdot \beta T' \\ &\leq (\alpha_1 \cdot \Phi^* + \alpha_2 \cdot T^*) + (1 + \epsilon) \beta \lambda \cdot T^* \\ &\leq (1 + \epsilon) \cdot \left[\alpha_1 \cdot \Phi^* + \left(\beta + \frac{\alpha_2}{\lambda} \right) \cdot \lambda T^* \right]. \end{aligned}$$

The first inequality follows from Property A(ii) in Definition 2.1; the second by the choice of $\tilde{T}$; the third by Property B (applied with threshold $T' \geq T^*$) in Definition 2.1, and using $T' \leq (1 + \epsilon) \cdot T^*$. Thus this algorithm for $\text{Robust}_k(\Pi)$ outputs a solution that is a $((1 + \epsilon) \cdot \max \{ \alpha_1, \beta + \frac{\alpha_2}{\lambda} \})$ -approximation. $\blacksquare$

In the rest of the paper, we focus on providing discriminating algorithms for suitable values of $\alpha_1, \alpha_2, \beta$.

2.2 Additional Property Needed for k -max-min Approximations

As we noted above, a k -max-min problem is a k -robust problem where the inflation $\lambda = 1$ (which implies that in an optimal solution $\Phi^* = 0$, and T^* is the k -max-min value). Hence a discriminating algorithm immediately gives an approximation to the value: for any $D \in \binom{[n]}{k}$, $\Phi_T \cup \text{Augment}_T(D)$ satisfies all demands in D , and for the right

guess of $T \approx T^*$, the cost is at most $(\alpha_2 + \beta)T^*$. It remains to output a bad k -set as well, and hence the following definition is useful.

Definition 2.3 *An algorithm for a robust problem is strongly discriminating if it satisfies the properties in Definition 2.1, and when the inflation parameter is $\lambda = 1$ (and hence $\Phi^* = 0$), the algorithm also outputs a set $Q_T \in \binom{[n]}{k}$ such that if $c(\Phi_T) \geq \alpha_2 T$, the cost of optimally covering the set Q_T is $\geq T$.*

Recall that for a covering problem Π , the cost of optimally covering the set of requirements $Q \in \binom{[n]}{k}$ is $\text{Opt}(Q) = \min\{c(E_Q) \mid E_Q \subseteq E \text{ and } E_Q \in \mathcal{R}_i \forall i \in Q\}$.

Lemma 2.4 *If there is an $(\alpha_1, \alpha_2, \beta)$ -strongly-discriminating algorithm for a robust covering problem $\text{Robust}_k(\Pi)$, then for every $\epsilon > 0$ there is an algorithm for k -max-min(Π) that outputs a set Q such that for some T , the optimal cost of covering this set Q is at least T , but every k -set can be covered with cost at most $(1 + \epsilon) \cdot (\alpha_2 + \beta) T$.*

Proof: The approximation algorithm for $\text{MaxMin}(\Pi)$ is similar to that in Lemma 2.2. Let $\mathcal{A}$ denote an algorithm for the robust problem that is $(\alpha_1, \alpha_2, \beta)$ strongly discriminating. Recall that the k -max-min instance corresponds to the $\text{Robust}_k(\Pi)$ instance with $\lambda = 1$, and hence we will run algorithm $\mathcal{A}$ on this robust instance. Also from Definition 2.1, T^* denotes the optimal second-stage cost of $\text{Robust}_k(\Pi)$, and its optimal first-stage cost $\Phi^* = 0$ (since $\lambda = 1$). Note that the optimal value of the k -max-min instance also equals T^* .

Let ground-set $E = [m]$, and $c_{\max} := \max_{e \in [m]} c_e$. By scaling, we may assume WLOG that all costs in the instance are integral. Let $\epsilon > 0$ be any value as given by the lemma (where $\frac{1}{\epsilon}$ is polynomially bounded), and $N := \lceil \log_{1+\epsilon} (m c_{\max}) \rceil + 1$; note that N is polynomial in the input size. Consider the integral powers of $(1 + \epsilon)$,

$$\mathcal{T} := \{t_i\}_{i=0}^N, \quad \text{where } t_i = (1 + \epsilon)^i \text{ for } i = 0, 1, \dots, N.$$

The approximation algorithm for $\text{MaxMin}(\Pi)$ runs the strongly discriminating algorithm $\mathcal{A}$ for every choice of $T \in \mathcal{T}$, and let $p \in \{1, \dots, N\}$ be the smallest index such that $c(\Phi(t_p)) \leq \alpha_2 t_p$. Observe that there must exist such an index since for all $T \geq T^*$, we have $c(\Phi_T) \leq \alpha_2 T^* \leq \alpha_2 T$ (property B in Definition 2.1, using $\Phi^* = 0$), and clearly $T^* \leq m \cdot c_{\max} \leq t_N$. The algorithm then outputs $Q(t_{p-1})$ as the max-min scenario. Below we prove that it achieves the claimed approximation. We have for all $T \geq 0$,

$$T^* = \max \left\{ \text{Opt}(D) : D \in \binom{[n]}{k} \right\} \leq \max \left\{ c(\Phi_T) + c(\text{Augment}_T(D)) : D \in \binom{[n]}{k} \right\} \leq c(\Phi_T) + \beta T.$$

Above, the inequalities are by conditions A(i) and A(ii) of Definition 2.1. Setting $T = t_p$ here, and by choice of p ,

$$T^* \leq c(\Phi(t_p)) + \beta t_p \leq (\alpha_2 + \beta) t_p.$$

Hence t_p is a $(\alpha_2 + \beta)$ -approximation to the max-min value T^* . Now applying the condition of Definition 2.3 with $T = t_{p-1}$, since $c(\Phi(t_{p-1})) \geq \alpha_2 t_{p-1}$ (by choice of index p), we obtain that the minimum cost to cover requirements $Q(t_{p-1})$ is at least:

$$t_{p-1} = \frac{t_p}{1 + \epsilon} \geq \frac{T^*}{(1 + \epsilon) \cdot (\alpha_2 + \beta)},$$

which implies the desired approximation guarantee. ■

3 k -Robust Set Cover

Consider the k -robust set cover problem where there is a set system $(U, \mathcal{F})$ with a universe of $|U| = n$ elements, and m sets in $\mathcal{F}$ with each set $R \in \mathcal{F}$ costing c_R , an inflation parameter λ , and an integer k such that each of the sets $\binom{U}{k}$ is a possible scenario for the second-stage. Given Lemma 2.2, it suffices to show a discriminating algorithm as defined in Definition 2.1 for this problem. The algorithm given below is easy: pick all elements which can only be covered by expensive sets, and cover them in the first stage.

Algorithm 1 Algorithm for k -Robust Set Cover

- 1: **input:** k -robust set-cover instance and threshold T .
 - 2: **let** $\beta \leftarrow 36 \ln m$, and $S \leftarrow \{v \in U \mid \text{min cost set covering } v \text{ has cost at least } \beta \cdot \frac{T}{k}\}$.
 - 3: **output** first stage solution Φ_T as the Greedy-Set-Cover(S).
 - 4: **define** $\text{Augment}_T(\{i\})$ as the min-cost set covering i , for $i \in U \setminus S$; and $\text{Augment}_T(\{i\}) = \emptyset$ for $i \in S$.
 - 5: **output** second stage solution Augment_T where $\text{Augment}_T(D) := \bigcup_{i \in D} \text{Augment}_T(\{i\})$ for all $D \subseteq U$.
-

Claim 3.1 (Property A for Set Cover) For all $T \geq 0$ and scenario $D \in \binom{U}{k}$, the sets $\Phi_T \cup \text{Augment}_T(D)$ cover elements in D , and have cost $c(\text{Augment}_T(D)) \leq \beta T$.

Proof: The elements in $D \cap S$ are covered by Φ_T ; and by definition of Augment_T , each element $i \in D \setminus S$ is covered by set $\text{Augment}_T(\{i\})$. Thus we have the first part of the claim. For the second part, note that by definition of S , the cost of $\text{Augment}_T(\{i\})$ is at most $\beta T/k$ for all $i \in U$. ■

Below $H_n := \sum_{i=1}^n \frac{1}{i} \approx \ln n$; recall that the greedy algorithm for set cover is an H_n -approximation where n is the number of elements in the given instance.

Theorem 3.2 (Property B for Set Cover) Let Φ^* denote the optimal first stage solution (and its cost), and T^* the optimal second stage cost. Let $\beta = 36 \ln m$. If $T \geq T^*$ then $c(\Phi_T) \leq H_n \cdot (\Phi^* + 12 \cdot T^*)$.

Proof: We claim that there is a fractional solution $\bar{x}$ for the set covering instance S with small cost $O(\Phi^* + T^*)$, whence rounding this to an integer solution implies the theorem. For a contradiction, assume not: let every fractional set cover be expensive, and hence there must be a dual solution of large value. We then round this dual solution to get a dual solution to a sub-instance with only k elements that costs $> \Phi^* + T^*$, which is impossible (since using the optimal solution we can solve every instance on k elements with that cost).

To this end, let $S' \subseteq S$ denote the elements that are *not* covered by the optimal first stage Φ^* , and let $\mathcal{F}' \subseteq \mathcal{F}$ denote the sets that contain at least one element from S' . By the choice of S , all sets in $\mathcal{F}'$ cost at least $\beta \cdot \frac{T}{k} \geq \beta \cdot \frac{T^*}{k}$. Define the “coarse” cost for a set $R \in \mathcal{F}'$ to be $\hat{c}_R = \lceil \frac{c_R}{\beta T^*/k} \rceil$. For each set $R \in \mathcal{F}'$, since $c_R \geq \frac{\beta T^*}{k} \geq \frac{6T^*}{k}$, it follows that $\hat{c}_R \cdot \frac{6T^*}{k} \in [c_R, 2 \cdot c_R]$, and also that $\hat{c}_R \geq \beta/6$.

Now consider the following primal-dual pair of LPs for the set cover instance with elements S' and sets $\mathcal{F}'$ having the coarse costs $\hat{c}$.

$$\begin{array}{ll} \min & \sum_{R \in \mathcal{F}'} \hat{c}_R \cdot x_R \\ & \sum_{R \ni e} x_R \geq 1, \quad \forall e \in S', \\ & x_R \geq 0, \quad \forall R \in \mathcal{F}'. \end{array} \qquad \begin{array}{ll} \max & \sum_{e \in S'} y_e \\ & \sum_{e \in R} y_e \leq \hat{c}_R, \quad \forall R \in \mathcal{F}', \\ & y_e \geq 0, \quad \forall e \in S'. \end{array}$$

Let $\{x_R\}_{R \in \mathcal{F}'}$ be an optimal primal and $\{y_e\}_{e \in S'}$ an optimal dual solution. The following claim bounds the (coarse) cost of these fractional solutions.

Claim 3.3 If $\beta = 36 \ln m$, then the LP cost is $\sum_{R \in \mathcal{F}'} \hat{c}_R \cdot x_R = \sum_{e \in S'} y_e \leq 2 \cdot k$.

Before we prove Claim 3.3, let us assume it and complete the proof of Theorem 3.2. Given the primal LP solution $\{x_R\}_{R \in \mathcal{F}'}$ to cover elements in S' , define an LP solution to cover elements in S as follows: define $z_R = 1$ if $R \in \Phi^*$, $z_R = x_R$ if $R \in \mathcal{F}' \setminus \Phi^*$; and $z_R = 0$ otherwise. Since the solution $\bar{z}$ contains Φ^* integrally, it covers elements $S \setminus S'$ (i.e. the portion of S covered by Φ^*); since $z_R \geq x_R$, $\bar{z}$ fractionally covers S' . Finally, the cost of this solution is $\sum_R c_R z_R \leq \Phi^* + \sum_R c_R x_R \leq \Phi^* + \frac{6T^*}{k} \cdot \sum_R \hat{c}_R x_R$. But Claim 3.3 bounds this by $\Phi^* + 12 \cdot T^*$. Since we have a LP solution of value $\Phi^* + 12T^*$, and the greedy algorithm is an H_n -approximation relative to the LP value for set cover, this completes the proof. ■

Claim 3.1 and Theorem 3.2 show our algorithm for set cover to be an $(H_n, 12H_n, 36 \ln m)$ -discriminating algorithm. Applying Lemma 2.2 converts this discriminating algorithm to an algorithm for k -robust set cover, and gives the following improvement to the result of [14].

Theorem 3.4 *There is an $O(\log m + \log n)$ -approximation for k -robust set cover.*

It remains to give the proof for Claim 3.3 above; indeed, that is where the technical heart of the result lies.

Proof of Claim 3.3: Recall that we want to bound the optimal fractional set cover cost for the instance $(S', \mathcal{F}')$ with the coarse (integer) costs; x_R and y_e are the optimal primal and dual solutions. For a contradiction, assume that the LP cost $\sum_{R \in \mathcal{F}'} \hat{c}_R x_R = \sum_{e \in S'} y_e$ lies in the unit interval $((\gamma - 1)k, \gamma k]$ for some integer $\gamma \geq 3$.

Define integer-valued random variables $\{Y_e\}_{e \in S'}$ by setting, for each $e \in S'$ independently, $Y_e = \lfloor y_e \rfloor + I_e$, where I_e is a Bernoulli($y_e - \lfloor y_e \rfloor$) random variable. We claim that whp the random variables $Y_e/3$ form a feasible dual—i.e., they satisfy all the constraints $\{\sum_{e \in R} (Y_e/3) \leq \hat{c}_R\}_{R \in \mathcal{F}'}$ with high probability. Indeed, consider a dual constraint corresponding to $R \in \mathcal{F}'$: since we have $\sum_{e \in R} \lfloor y_e \rfloor \leq \hat{c}_R$, we get that $\Pr[\sum_{e \in R} Y_e > 3 \cdot \hat{c}_R] \leq \Pr[\sum_{e \in R} I_e > 2 \cdot \hat{c}_R]$. But now we use a Chernoff bound [28] to bound the probability that the sum of independent 0-1 r.v.s, $\sum_{e \in R} I_e$, exceeds twice its mean (here $\sum_{e \in R} E[I_e] \leq \sum_{e \in R} y_e \leq \hat{c}_R$) by $e^{-\hat{c}_R/3} \leq e^{-\beta/18} \leq m^{-2}$, since each $\hat{c}_R \geq \beta/6$ and $\beta = 36 \cdot \ln m$. Finally, a trivial union bound implies that $Y_e/3$ satisfies all the m constraints with probability at least $1 - 1/m$. Moreover, the expected dual objective is $\sum_{e \in S'} y_e \geq (\gamma - 1)k \geq 1$ (since $\gamma \geq 3$ and $k \geq 1$), and by another Chernoff Bound, $\Pr[\sum_{e \in S'} Y_e > \frac{\gamma-1}{2} \cdot k] \geq a$, where $a > 0$ is some constant. Putting it all together, with probability at least $a - \frac{1}{m}$, we have a *feasible* dual solution $Y'_e := Y_e/3$ with objective value at least $\frac{\gamma-1}{6} \cdot k$.

Why is this dual Y'_e any better than the original dual y_e ? It is “near-integral”—specifically, each Y'_e is either zero or at least $\frac{1}{3}$. So order the elements of S' in decreasing order of their Y' -value, and let Q be the set of the *first* k elements in this order. The total dual value of elements in Q is at least $\min\{\frac{\gamma-1}{6}k, \frac{k}{3}\} \geq \frac{k}{3}$, since $\gamma \geq 3$, and each non-zero Y' value is $\geq 1/3$. This valid dual for elements in Q shows a lower bound of $\frac{k}{3}$ on minimum (fractional) $\hat{c}$ -cost to cover the k elements in Q . Using $c_R > \frac{3T^*}{k} \cdot \hat{c}_R$ for each $R \in \mathcal{F}'$, the minimum c -cost to fractionally cover Q is $> \frac{3T^*}{k} \cdot \frac{k}{3} = T^*$. Hence, if Q is the realized scenario, the optimal second stage cost will be $> T^*$ (as no element in Q is covered by Φ^*)—this contradicts the fact that OPT can cover $Q \in \binom{U}{k}$ with cost at most T^* . Thus we must have $\gamma \leq 2$, which completes the proof of Claim 3.3. ■

The k -Max-Min Set Cover Problem. The proof of Claim 3.3 suggests how to get a $(H_n, 12H_n, 36 \ln m)$ strongly discriminating algorithm. When $\lambda = 1$ (and so $\Phi^* = 0$), the proof shows that if $c(\Phi_T) > 12H_n \cdot T$, there is a randomized algorithm that outputs k -set Q with optimal covering cost $> T$ (witnessed by the dual solution having cost $> T$). Now using Lemma 2.4, we get the claimed $O(\log m + \log n)$ algorithm for the k -max-min set cover problem. This nearly matches the hardness of $\Omega(\frac{\log m}{\log \log m} + \log n)$ given by [14].

Remarks: The result above (as well as the [14] result) also hold in the presence of set-dependent inflation factors—details appear in Appendix B. Results for the other covering problems do not extend to the case of non-uniform inflation: this is usually inherent, and not just a flaw in our analysis. Eg., [27] give an $\Omega(\log^{1/2-\epsilon} n)$ hardness for k -robust Steiner forest under just two distinct inflation-factors, whereas we give an $O(1)$ -approximation under uniform inflations (in Section 6).

4 k -Robust Minimum Cut

We now consider the k -robust minimum cut problem, where we are given an undirected graph $G = (V, E)$ with edge capacities $c : E \rightarrow \mathbb{R}_+$, a root $r \in V$, terminals $U \subseteq V$, inflation factor λ . Again, any subset in $\binom{U}{k}$ is a possible second-stage scenario, and again we seek to give a discriminating algorithm. This algorithm, like for set cover, is non-adaptive: we just pick all the “expensive” terminals and cut them in the first stage.

Claim 4.1 (Property A for Min-Cut) *For all $T \geq 0$ and $D \in \binom{U}{k}$, the edges $\Phi_T \cup \text{Augment}_T(D)$ separate the terminals D from r ; moreover, the cost $c(\text{Augment}_T(D)) \leq \beta T$.*

Theorem 4.2 (Property B for Min-Cut) *Let Φ^* denote the optimal first stage solution (and its cost), and T^* the optimal second stage cost. If $\beta \geq \frac{10e}{e-1}$ and $T \geq T^*$ then $c(\Phi_T) \leq 3 \cdot \Phi^* + \frac{\beta}{2} \cdot T^*$.*

Algorithm 2 Algorithm for k -Robust Min-Cut

- 1: **input:** k -robust minimum-cut instance and threshold T .
 - 2: **let** $\beta \leftarrow \Theta(1)$, and $S \leftarrow \{v \in U \mid \text{min cut separating } v \text{ from root } r \text{ has cost at least } \beta \cdot \frac{T}{k}\}$.
 - 3: **output** first stage solution Φ_T as the minimum cut separating S from r .
 - 4: **define** $\text{Augment}_T(\{i\})$ as the min- r - i cut in $G \setminus \Phi_T$, for $i \in U \setminus S$; and $\text{Augment}_T(\{i\}) = \emptyset$ for $i \in S$.
 - 5: **output** second stage solution Augment_T where $\text{Augment}_T(D) := \bigcup_{i \in D} \text{Augment}_T(\{i\})$ for all $D \subseteq U$.
-

Here's the intuition for this theorem: As in the set cover proof, we claim that if the optimal cost of separating S from the root r is high, then there must be a dual solution (which prescribes flows from vertices in S to r) of large value. We again "round" this dual solution by aggregating these flows to get a set of k terminals that have a large combined flow (of value $> \Phi^* + T^*$) to the root—but this is impossible, since the optimal solution promises us a cut of at most $\Phi^* + T^*$ for any set of k terminals.

However, more work is required. For set-cover, each element was either covered by the first-stage, or it was not; for cut problems, things are not so cut-and-dried, since both stages may help in severing a terminal from the root! So we divide S into two parts differently: the first part contains those nodes whose min-cut in G is large (since they belonged to S) but it fell by a constant factor in the graph $G \setminus \Phi^*$. These we call "low" nodes, and we use a Gomory-Hu tree based analysis to show that all low nodes can be completely separated from r by paying only $O(\Phi^*)$ more (this we show in Claim 4.3). The remaining "high" nodes continue to have a large min-cut in $G \setminus \Phi^*$, and for these we use the dual rounding idea sketched above to show a min-cut of $O(T^*)$ (this is proved in Claim 4.4). Together these claims imply Theorem 4.2.

To begin the proof of Theorem 4.2, let $H := G \setminus \Phi^*$, and let $S_h \subseteq S$ denote the "high" vertices whose min-cut from the root in H is at least $M := \frac{\beta}{2} \cdot \frac{T^*}{k}$. The following claim is essentially from Golovin et al. [20].

Claim 4.3 (Cutting Low Nodes) *If $T \geq T^*$, the minimum cut in H separating $S \setminus S_h$ from r costs at most $2 \cdot \Phi^*$.*

Proof: Let $S' := S \setminus S_h$, and $t := \beta \cdot \frac{T^*}{k}$. For every $v \in S'$, the minimum $r - v$ cut is at least $\beta \cdot \frac{T}{k} \geq \beta \cdot \frac{T^*}{k} = 2M$ in G , and at most M in H . Consider the Gomory-Hu (cut-equivalent) tree $\mathcal{T}(H)$ on graph H rooted at r [32, Chap. 15]. For each $u \in S'$ let $D_u \subseteq V$ denote the minimum $r - u$ cut in $\mathcal{T}(H)$ where $u \in D_u$ and $r \notin D_u$. Pick a subset $S'' \subseteq S'$ of terminals such that the union of their respective min-cuts in $\mathcal{T}(H)$ separate all of S' from the root and their corresponding sets D_u are disjoint (the set of cuts in tree $\mathcal{T}(H)$ closest to the root r gives such a collection). It follows that (a) $\{D_u \mid u \in S''\}$ are disjoint, and (b) $F := \bigcup_{u \in S''} \partial_H(D_u)$ is a feasible cut in H separating S' from r . Note that for all $u \in S''$, we have $c(\partial_H(D_u)) \leq M$ (since it is a minimum r - u cut in H), and $c(\partial_G(D_u)) \geq 2M$ (it is a feasible r - u cut in G). Thus $c(\partial_H(D_u)) \leq c(\partial_G(D_u)) - c(\partial_H(D_u)) = c(\partial_{\Phi^*}(D_u))$. Now, $c(F) \leq \sum_{u \in S''} c(\partial_H(D_u)) \leq \sum_{u \in S''} c(\partial_{\Phi^*}(D_u)) \leq 2 \cdot \Phi^*$. The last inequality uses disjointness of $\{D_u\}_{u \in S''}$. Thus the minimum $r - S'$ cut in H is at most $2\Phi^*$. ■

Claim 4.4 (Cutting High Nodes) *If $T \geq T^*$, the minimum r - S_h cut in H costs at most $\frac{\beta}{2} \cdot T^*$, when $\beta \geq \frac{10 \cdot e}{e-1}$.*

Proof: Consider an r - S_h max-flow in the graph $H = G \setminus \Phi^*$, and suppose it sends $\alpha_i \cdot M$ flow to vertex $i \in S_h$. By making copies of terminals, we can assume each $\alpha_i \in (0, 1]$; the k -robust min-cut problem remains unchanged under making copies. Hence if we show that $\sum_{i \in S_h} \alpha_i \leq k$, the total flow (which equals the min r - S_h cut) would be at most $k \cdot M = \frac{\beta}{2} \cdot T^*$, which would prove the claim. For a contradiction, we suppose that $\sum_{i \in S_h} \alpha_i > k$. We will now claim that there exists a subset $W \subseteq S_h$ with $|W| \leq k$ such that the min r - W cut is more than T^* , contradicting the fact that every k -set in H can be separated from r by a cut of value at most T^* . To find this set W , the following redistribution lemma (proved at the end of this theorem) is useful.

Lemma 4.5 (Redistribution Lemma) *Let $N = (V, E)$ be a capacitated undirected graph. Let $X \subseteq V$ be a set of terminals such $\text{min-cut}_N(i, j) \geq 1$ for all nodes $i, j \in X$. For each $i \in X$, we are given a value $\epsilon_i \in (0, 1]$. Then for any integer $\ell \leq \sum_{i \in X} \epsilon_i$, there exists a subset $W \subseteq X$ with $|W| \leq \ell$ vertices, and a feasible flow f in N from X to W so that (i) the total f -flow into W is at least $\frac{1-e^{-1}}{4} \cdot \ell$ and (ii) the f -flow out of each $i \in X$ is at most $\epsilon_i/4$.*

We apply this lemma to $H = G \setminus \Phi^*$ with terminal set S_h , but with capacities scaled down by M . Since for any cut separating $x, y \in S_h$, the root r lies on one side on this cut (say on y 's side), $\min\text{-cut}_H(x, y) \geq M$ —hence the scaled-down capacities satisfy the conditions of the lemma. Now set $\ell = k$, and $\epsilon_i := \alpha_i$ for each terminal $i \in S_h$; by the assumption $\sum_{i \in S_h} \epsilon_i = \sum_{i \in S_h} \alpha_i \geq k = \ell$. Hence Lemma 4.5 finds a subset $W \subseteq S_h$ with k vertices, and a flow f in (unscaled) graph H such that f sends a total of at least $\frac{1-1/e}{4} \cdot kM$ units into W , and at most $\frac{\alpha_i}{4} \cdot M$ units out of each $i \in S_h$. Also, there is a feasible flow g in the network H that simultaneously sends $\alpha_i \cdot M$ flow from the root to each $i \in S_h$, namely the max-flow from r to S_h . Hence the flow $\frac{g+4f}{5}$ is feasible in H , and sends at least $\frac{4}{5} \cdot \frac{1-1/e}{4} \cdot kM = \frac{1-1/e}{5} \cdot kM$ units from r into W . Finally, if $\beta > \frac{10 \cdot e}{e-1}$, we obtain that the min-cut in H separating W from r is greater than T^* : since $|W| \leq k$, this is a contradiction to the assumption that any set with at most k vertices can be separated from the root in H at cost at most T^* . ■

From Claim 4.1 and Theorem 4.2, we obtain a $(3, \frac{\beta}{2}, \beta)$ -discriminating algorithm for k -robust minimum cut, when $\beta \geq \frac{10e}{e-1}$. We set $\beta = \frac{10e}{e-1}$ and use Lemma 2.2 to infer that the approximation ratio of this algorithm is $\max\{3, \frac{\beta}{2\lambda} + \beta\} = \frac{\beta}{2\lambda} + \beta$. Since picking edges only in the second-stage is a trivial λ -approximation, the better of the two gives an approximation of $\min\{\frac{\beta}{2\lambda} + \beta, \lambda\} < 17$. Thus we have,

Theorem 4.6 (Min-cut Theorem) *There is a 17-approximation algorithm for k -robust minimum cut.*

It now remains to prove the redistribution lemma. At a high level, the proof shows that if we add each vertex $i \in X$ to a set W independently with probability $\epsilon_i \ell / (\sum_i \epsilon_i)$, then this set W will (almost) satisfy the conditions of the lemma whp. A natural approach to prove this would be to invoke Gale/Hoffman-type theorems [32, Chap. 11]: e.g., it is necessary and sufficient to show that $c(\partial V') \geq |\text{demand}(V') - \text{supply}(V')|$ for all $V' \subseteq V$ for this random choice W . But we need to prove such facts for *all* subsets, and all we know about the network is that the min-cut between any pair of nodes in X is at least 1! Also, such a general approach is likely to fail, since the redistribution lemma is false for directed graphs (see remark at the end of this section) whereas the Gale-Hoffman theorems hold for digraphs. In our proof, we use undirectedness to fractionally pack Steiner trees into the graph, on which we can do a randomized-rounding-based analysis.

Proof of Lemma 4.5 (Redistribution Lemma): To begin, we assume w.l.o.g. that the bounds $\epsilon_i = 1/P$ for all $i \in X$ for some integer P . Indeed, let $P \in \mathbb{N}$ be large enough so that $\hat{\epsilon}_i = \epsilon_i P$ is an integer for each $i \in X$. Add, for each $i \in X$, a star with $\hat{\epsilon}_i - 1$ leaves centered at the original vertex i , set all these new vertices to also be terminals, and let all new edges have unit capacity. Set the new ϵ 's to be $1/P$ for all terminals. To avoid excess notation, call this graph N as well; note that the assumptions of the lemma continue to hold, and any solution W on this new graph can be mapped back to the original graph.

Let c_e denote the edge capacities in N , and recall the assumption that every cut in N separating X has capacity at least one. Since the natural LP relaxation for Steiner-tree has integrality gap of 2, this implies the existence of Steiner trees $\{T_a\}_{a \in A}$ on the terminal set X that fractionally pack into the edge capacities $\bar{c}$. I.e., there exist positive multipliers $\{\lambda_a\}_{a \in A}$ such that $\sum_a \lambda_a = \frac{1}{2}$, and $\sum_a \lambda_a \cdot \bar{\chi}(T_a) \leq \bar{c}$, where $\bar{\chi}(T_a)$ is the characteristic vector of the tree T_a . Choose $W \subseteq X$ by taking ℓ samples uniformly at random (with replacement) from X . We will construct the flow f from X to W as a sum of flows on these Steiner trees. In the following, let $q := |X|$; note that $\ell \leq |X| \epsilon = q/P$.

Consider any fixed tree T_a in this collection, where we think of the edges as having unit capacities. We claim that in expectation, $\Omega(\ell)$ units of flow can be feasibly routed from X to W in T_a such that each terminal supplies at most ℓ/q . Indeed, let τ_a denote an oriented Euler tour corresponding to T_a . Since the tour uses any tree edge twice, any feasible flow routed in τ_a (with unit-capacity edges) can be scaled by half to obtain a feasible flow in T_a . We call a vertex $v \in X$ *a-close* if there is some W -vertex located at most q/ℓ hops from v on the (oriented) tour τ_a . Construct a flow f_a on τ_a by sending ℓ/q flow from each *a-close* vertex $v \in X$ to its nearest W -vertex along τ_a . By the definition of *a-closeness*, the maximum number of flow paths in f_a that traverse an edge on τ_a is q/ℓ ; since each flow path carries ℓ/q flow, the flow on any edge in τ_a is at most one, and hence f_a is always feasible.

For any vertex $v \in X$ and a tour τ_a , the probability that v is *not* a -close is at most $(1 - \frac{q/\ell}{q})^\ell \leq e^{-1}$; hence $v \in X$ sends flow in f_a with probability at least $1 - e^{-1}$. Thus the expected amount of flow sent in f_a is at least $(1 - e^{-1})|X| \cdot (\ell/q) = (1 - e^{-1}) \cdot \ell$. Now define the flow $f := \frac{1}{2} \sum_a \lambda_a \cdot f_a$ by combining all the flows along all the Steiner trees. It is easily checked that this is a feasible flow in N with probability one. Since $\sum_a \lambda_a = \frac{1}{2}$, the expected value of flow f is at least $\frac{1-1/e}{4} \ell$. Finally the amount of flow in f sent out of any terminal is at most $\frac{1}{4} \cdot \ell/q \leq \frac{1}{4P}$. This completes the proof of the redistribution lemma. ■

The k -max-min Min-Cut Problem. When $\lambda = 1$ and $\Phi^* = 0$, the proof of Theorem 4.2 gives a randomized algorithm such that if the minimum r - S cut is greater than $\frac{\beta}{2}T$, it finds a subset W of at most k terminals such that separating W from the root costs more than T (witnessed by the dual value). Using this we get a randomized $(3, \frac{\beta}{2}, \beta)$ strongly discriminating algorithm, and hence a randomized $O(1)$ -approximation algorithm for k -max-min min cut from Lemma 2.4. We note that for k -max-min min-cut, a $(1 - 1/e)$ -approximation algorithm was already known (even for directed graphs) via submodular maximization. However the above approach has the advantage that it also extends to k -robust min-cut.

Bad Example for Directed Graphs. Let us show that our theorems for k -robust min-cut have to use the undirectedness of the graph crucially, and that the theorems are in fact false for directed graphs. Consider the digraph G with a root r , a “center” vertex c , and ℓ terminals $v_1, v_2, \dots, v_\ell$. This graph has arcs are (c, r) , $\{(r, v_i)\}_{i \in [\ell]}$ and $\{(v_i, c)\}_{i \in [\ell]}$; each having unit capacity. Note that the min-cut between every v_i - v_j pair is 1, but if we give each of the v_i ’s $\epsilon_i = 1/\sqrt{\ell}$ flow, there is no way to choose $\sqrt{\ell}$ of these vertices and collect a total of $\Omega(\sqrt{\ell})$ flow at these “leaders”. This shows that the redistribution lemma (Lemma 4.5) is false for digraphs.

A similar example shows that thresholded algorithms perform poorly for k -robust directed min-cut, even for $k = 1$. Consider graph D with vertices r, c and $\{v_i\}_{i \in [\ell]}$ as above. Graph D has unit capacity arcs $\{(v_i, r)\}_{i \in [\ell]}$, and $\sqrt{\ell}$ capacity arcs (c, r) and $\{(v_i, c)\}_{i \in [\ell]}$. The inflation factor is $\lambda = \sqrt{\ell}$. The optimal strategy is to delete the arc (c, r) in the first stage. Since $k = 1$, one of the terminals v_i demands to be separated from the root in the second stage, whence deleting the edge (v_i, r) costs $\lambda \cdot 1 = \sqrt{\ell}$ resulting in a total cost of $2\sqrt{\ell}$. However, any threshold-based algorithm would either choose none of the terminals (resulting in a recourse cost of $\lambda\sqrt{\ell} = \ell$), or all of them (resulting in a first-stage cost of at least ℓ).

5 k -Robust Multicut

We now consider the multicut problem: we are given an undirected graph $G = (V, E)$ with edge-costs $c : E \rightarrow \mathbb{R}_+$, and m vertex-pairs $\{s_i, t_i\}_{i=1}^m$. In the k -robust version, we are also given an inflation parameter λ and bound k on the cardinality of the realized demand-set. Let Φ^* denote the optimal first stage solution (and its cost), and T^* the optimal second stage cost; so $\text{Opt} = \Phi^* + \lambda \cdot T^*$. The algorithm (given below) is essentially the same as for minimum cut, however the analysis requires different arguments.

Algorithm 3 Algorithm for k -Robust MultiCut

- 1: **input:** k -robust multicut instance and threshold T .
 - 2: **let** $\rho := O(\log n)$ be the approximation factor in Räcke’s oblivious routing scheme [30], $\epsilon \in (0, \frac{1}{2})$ any constant, and $\beta := \rho \cdot \frac{16 \log n}{\epsilon \log \log n}$.
 - 3: **let** $S \leftarrow \{i \in [m] \mid \min s_i - t_i \text{ cut has cost at least } \beta \cdot \frac{T}{k}\}$.
 - 4: **output** first stage solution Φ_T as the $O(\log n)$ -approximate multicut [18] for S .
 - 5: **define** $\text{Augment}_T(\{i\})$ as edges in the min $s_i - t_i$ cut, for $i \in [m] \setminus S$; and $\text{Augment}_T(\{i\}) = \emptyset$ for $i \in S$.
 - 6: **output** second stage solution Augment_T where $\text{Augment}_T(\omega) := \bigcup_{i \in \omega} \text{Augment}_T(\{i\})$ for all $\omega \subseteq [m]$.
-

Claim 5.1 (Property A for Multicut) *For all $T \geq 0$ and $\omega \subseteq [m]$, the edges $\Phi_T \cup \text{Augment}_T(\omega)$ separate s_i and t_i for all $i \in \omega$; additionally if $|\omega| \leq k$ then the cost $c(\text{Augment}_T(\omega)) \leq \beta T$.*

Proof: Pairs in $\omega \cap S$ are separated by Φ_T . By definition of Augment_T , for each pair $i \in \omega \setminus S$ edges $\text{Augment}_T(\{i\})$ form an $s_i - t_i$ cut. Thus we have the first part of the claim. For the second part, note that by definition of S , the cost of $\text{Augment}_T(\{i\})$ is at most $\beta T/k$ for all $i \in [m]$. ■

Theorem 5.2 (Property B for Multicut) *If $T \geq T^*$ then $c(\Phi_T) \leq O(\log n) \cdot \Phi^* + O(\log^{2+\epsilon} n) \cdot T^*$.*

To prove the theorem, the high level approach is similar to that for k -robust min-cut. We first show in Lemma 5.3 that the subset of pairs $\tilde{S} \subseteq S$ whose min-cut fell substantially on deleting the edges in Φ^* can actually be completely separated by paying $O(1)\Phi^*$. This is based on a careful charging argument on the Gomory-Hu tree and generalizes the [20] lemma from min-cut to multicut. Then in Lemma 5.6 we show that the remaining pairs in $S \setminus \tilde{S}$ can be *fractionally* separated at cost $O(\log^{1+\epsilon} n) T^*$. This uses the dual-rounding approach combined with Räcke's oblivious routing scheme [30]. Finally since the [18] algorithm for multicut is relative to the LP, this would imply Theorem 5.2.

Let us begin by formally defining the cast of characters. Let $H := G \setminus \Phi^*$ and $M := \beta \cdot \frac{T^*}{k}$. Define,

$$\tilde{S} := \{i \in S \mid \text{min cost } s_i - t_i \text{ cut in } H \text{ is less than } \frac{M}{4}\}$$

to be the set of pairs whose mincut in G was at least M , but has fallen to at most $M/4$ in $H = G \setminus \Phi^*$.

Lemma 5.3 *If $T \geq T^*$, there is a multicut separating pairs $\tilde{S}$ in graph H which has cost at most $2\Phi^*$.*

Proof: We work with graph $H = (V, F)$ with edge-costs $c : F \rightarrow \mathbb{R}$. A *cluster* refers to any subset of vertices. A *cut equivalent tree* (c.f. [10]), $P = (\mathcal{N}(P), E(P))$ is an edge-weighted tree on clusters $\mathcal{N}(P) = \{N_j\}_{j=1}^r$ such that:

- the clusters $\{N_j\}_{j=1}^r$ form a partition of V , and
- for any edge $e \in E(P)$, its weight in P equals the c -cost of the cut corresponding to deleting this edge in P . I.e., if (S_e, S_e^c) is the partition of V obtained by unioning the vertices in the clusters belonging to the two connected components of $P \setminus \{e\}$, then e 's weight in P equals $c(\delta(S_e)) = c(\delta(S_e^c))$.

The *Gomory-Hu tree* $P_{GH} = (V, E(P_{GH}))$ of H is a cut-equivalent tree where the clusters are singleton vertices, and which has the additional property that for every $u, v \in V$ the minimum $u-v$ cut in P_{GH} equals the minimum $u-v$ cut in H . For any cut-equivalent tree, a cluster $N \subseteq V$ is called *active* if there is some $i \in \tilde{S}$ such that $|N \cap \{s_i, t_i\}| = 1$; otherwise the cluster N is called *dead*. We obtain a cut-equivalent tree Q from P_{GH} by repeatedly performing one of the following modifications: (1) for each edge having weight greater than $\frac{M}{4}$, merge the clusters corresponding to its end points; and (2) for each dead cluster, merge it with any of its neighboring clusters. Note that in the resulting tree Q , every edge in $E(Q)$ has weight at most $\frac{M}{4}$, and every cluster in $\mathcal{N}(Q)$ is active. Let $\mathcal{D} := \bigcup_{N \in \mathcal{N}(Q)} \partial_H(N)$. In the next two claims we show that $\mathcal{D}$ is a feasible multicut for $\tilde{S}$ with cost at most $2\Phi^*$.

Claim 5.4 *$\mathcal{D}$ is a feasible multicut separating pairs $\tilde{S}$ in H .*

Proof: Clearly for each pair $i \in \tilde{S}$, vertices s_i and t_i are in distinct active clusters of the Gomory-Hu tree P_{GH} . Additionally there is some edge of weight less than $\frac{M}{4}$ on the $s_i - t_i$ path in P_{GH} : since the minimum $s_i - t_i$ cut in H is less than $\frac{M}{4}$. Observe that in obtaining tree Q from P_{GH} , we never contract two active clusters nor an edge of weight less than $\frac{M}{4}$. Thus s_i and t_i lie in distinct clusters of Q . Since this holds for all $i \in \tilde{S}$, the claim follows by definition of $\mathcal{D}$. ■

Claim 5.5 *The cost $c(\mathcal{D}) = \sum_{e \in \mathcal{D}} c_e \leq 2\Phi^*$, if $T \geq T^*$.*

Proof: Consider any cluster $N \in \mathcal{N}(Q)$. Since all clusters in $\mathcal{N}(Q)$ are active, N contains exactly one of $\{s_i, t_i\}$ for some $i \in \tilde{S}$. Hence the cut $\partial_G(N)$ (in graph G) has cost at least $\beta \cdot \frac{T}{k} \geq \beta \cdot \frac{T^*}{k} = M$, by definition of the set $S \supseteq \tilde{S}$.

Let $\mathcal{N}_2(Q) \subseteq \mathcal{N}(Q)$ denote all clusters in Q having degree at most two in Q . Note that $|\mathcal{N}_2(Q)| \geq \frac{1}{2}|\mathcal{N}(Q)|$. Using the above observation and the fact that clusters in $\mathcal{N}_2(Q)$ are disjoint, we have

$$|\mathcal{N}_2(Q)| M \leq \sum_{N \in \mathcal{N}_2(Q)} c(\partial_G(N)) = \sum_{N \in \mathcal{N}_2(Q)} (c(\partial_H(N)) + c(\partial_{\Phi^*}(N))) \leq \sum_{N \in \mathcal{N}_2(Q)} c(\partial_H(N)) + 2\Phi^*. \quad (5.1)$$

We now claim that for any $N \in \mathcal{N}_2(Q)$, the cost $c(\partial_H(N)) \leq \frac{M}{2}$. Let e_1 and e_2 denote the two edges incident to cluster N in Q (the case of a single edge is easier). Let $(U_l, V \setminus U_l)$ denote the cut corresponding to edge e_l (for $l = 1, 2$) where $N \subseteq U_l$. Each of these cuts has cost $c(\partial_H(U_l)) \leq \frac{M}{4}$ by property of cut-equivalent tree Q , and their union $\partial_H(U_1) \cup \partial_H(U_2)$ is the cut separating N from $V \setminus N$. Hence it follows that $c(\partial_H(N)) \leq 2 \cdot \frac{M}{4} = \frac{M}{2}$. Using this in (5.1) and simplifying, we obtain $|\mathcal{N}(Q)| M \leq 2 \cdot |\mathcal{N}_2(Q)| M \leq 8\Phi^*$.

For each edge $e \in E(Q)$, let $D_e \subseteq F$ denote the edges in graph H that go across the two components of $Q \setminus \{e\}$. By the property of cut-equivalent tree Q , we have $c(D_e) \leq \frac{M}{4}$. Since $\mathcal{D} = \bigcup_{e \in E(Q)} D_e$,

$$c(\mathcal{D}) \leq \sum_{e \in E(Q)} c(D_e) \leq |E(Q)| \frac{M}{4} \leq |\mathcal{N}(Q)| \frac{M}{4} \leq 2\Phi^*$$

This proves the claim. ■

Combining Claims 5.4 and 5.5, we obtain the lemma. ■

Now we turn our attention to the remaining pairs $W := S \setminus \tilde{S}$, and show that there is a cheap cut separating them in H . For this we use a dual-rounding argument, based on Räcke's oblivious routing scheme. Recall that constant $0 < \epsilon < \frac{1}{2}$, $\rho = O(\log n)$ (Räcke's approximation factor), and $\beta = \rho \cdot \frac{16 \log n}{\epsilon \log \log n}$. Define $\alpha := \epsilon \rho \cdot \log^\epsilon n$.

Lemma 5.6 *There exists a fractional multicut separating pairs W in the graph H which has cost $8\alpha \cdot T^*$.*

Proof: For any demand vector $d : W \rightarrow \mathbb{R}_+$, the optimal *congestion* of routing d in H , denoted $\text{Cong}(d)$, is the smallest $\eta \geq 0$ such that there is a flow routing d_i units of flow between s_i and t_i (for each $i \in W$), using capacity at most $\eta \cdot c_e$ on each edge $e \in H$. Note that for every $i \in W$, the s_i - t_i min-cut in H has cost at least $L := \frac{M}{4} = \frac{\beta}{4} \cdot \frac{T^*}{k}$. Hence for any $i \in W$, the optimal congestion for a *unit* demand between s_i - t_i (and zero between all other pairs) is at most $\frac{1}{L}$.

Now consider Räcke's oblivious routing scheme [30] as applied to graph H . This routing scheme, for each $i \in W$, prescribes a unit flow $\mathcal{F}_i$ between s_i - t_i such that for every demand vector $d : W \rightarrow \mathbb{R}_+$,

$$\max_{e \in H} \frac{\sum_{i \in W} d_i \cdot \mathcal{F}_i(e)}{c_e} \leq \rho \cdot \text{Cong}(d), \quad \text{where } \rho = O(\log n);$$

i.e., the congestion achieved by using these oblivious templates to route the demand d is at most ρ times the best congestion possible for that particular demand d .

Now consider a maximum multicommodity flow in H ; suppose that it sends $y_i \cdot \frac{T^*}{k}$ units between s_i, t_i for each $i \in W$. For a contradiction, suppose that $\sum_{i \in W} y_i > 8\alpha \cdot k$. (Otherwise the maximum multicommodity flow, and hence its dual, the minimum fractional multicut is at most $8\alpha T^*$, and the lemma holds.) By making copies of vertex-pairs, we may assume that $y_i \in [0, 1]$ for all $i \in W$; this does not change the k -robust multicut instance. Define a (not necessarily feasible) multicommodity flow $\mathcal{G} := \sum_{i \in W} X_i \cdot \frac{T^*}{k} \cdot \mathcal{F}_i$, where each X_i is an independent 0-1 random variable with $\Pr[X_i = 1] = \frac{y_i}{\alpha}$, and $\mathcal{F}_i$ is the Räcke oblivious routing template. The flow has expected magnitude at least $\sum_i \frac{y_i}{\alpha} \frac{T^*}{k} \geq 8T^*$, and is the sum of $\{0, \frac{T^*}{k}\}$ -valued random variables, hence by a Chernoff bound:

Claim 5.7 *With constant probability, the magnitude of flow $\mathcal{G}$ is at least T^* .*

Claim 5.8 *The flow $\mathcal{G}$ is feasible with probability $1 - o(1)$.*

Proof: Fix any edge $e \in H$, and let $u_i(e) := \frac{T^*}{k} \cdot \mathcal{F}_i(e)$ for all $i \in W$. Note that the random process gives us a flow of $\sum_i X_i \cdot u_i(e)$ on the edge e . The feasibility of the maximum multicommodity flow says that $\text{Cong}(\{y_i \cdot \frac{T^*}{k}\}_{i \in W}) \leq 1$. Since oblivious routing loses only a ρ factor in the congestion,

$$\sum_{i \in W} y_i \cdot u_i(e) = \sum_{i \in W} y_i \cdot \frac{T^*}{k} \cdot \mathcal{F}_i(e) \leq \rho \cdot c_e;$$

and the expected flow on edge e sent by the random process above is $\sum_{i \in W} \frac{y_i}{\alpha} \cdot u_i(e) \leq \frac{\rho}{\alpha} c_e$.

Now, since the min s_i - t_i -cut is at least L for any $i \in W$, a unit of flow can (non-obliviously) be sent between s_i, t_i at congestion at most $\frac{1}{L}$. Hence using the oblivious routing template $\mathcal{F}_i$ incurs a congestion at most $\frac{\rho}{L}$. Hence,

$$u_i(e) = \frac{T^*}{k} \cdot \mathcal{F}_i(e) \leq \frac{T^*}{k} \cdot \frac{\rho}{L} \cdot c_e = \frac{4\rho}{\beta} \cdot c_e$$

We divide the individual contributions by the edge capacity and further scale up by $\frac{\beta}{4\rho}$ by defining new $[0, 1]$ -random variables $Y_i = \frac{X_i \cdot u_i(e)}{c_e} \cdot \frac{\beta}{4\rho}$. We get that $\mu := E[\sum Y_i] \leq \frac{\beta}{4\alpha}$. Recall the Chernoff bound that says that for independent $[0, 1]$ -valued random variables Y_i ,

$$\Pr \left[\sum Y_i \geq (1 + \delta) \cdot \mu \right] \leq \left(\frac{e}{1 + \delta} \right)^{\mu(1 + \delta)}$$

Using this with $\mu(1 + \delta) = \frac{\beta}{4\rho}$ (hence $\delta + 1 \geq \frac{\alpha}{\rho}$) we get that

$$\Pr \left[\sum_i X_i \cdot u_i(e) \geq c_e \right] = \Pr \left[\sum_i Y_i \geq \frac{\beta}{4\rho} \right] \leq \left(\frac{e\rho}{\alpha} \right)^{\beta/4\rho} = \exp \left(-\epsilon \log \log n \cdot \frac{4 \log n}{\epsilon \log \log n} \right) = \frac{1}{n^4},$$

since $\alpha = e\rho \cdot \log^\epsilon n$ and $\beta = \rho \cdot \frac{16 \log n}{\epsilon \log \log n}$. Now a trivial union bound over all n^2 edges gives the claim. ■

By another union bound, it follows that there exists a feasible multicommodity flow $\mathcal{G}$ that sends either zero or $\frac{T^*}{k}$ units for each pair $i \in W$, and the total value of $\mathcal{G}$ is at least T^* . Hence there exists some k -set $W' \subseteq W$ such that the maximum multicommodity flow for W' on H is at least T^* . This contradicts the fact that every k -set has a multicut of cost less than T^* in H . Thus we must have $\sum_{i \in W} y_i \leq 8\alpha \cdot k$, which implies Lemma 5.6. ■

Combining Lemmas 5.3 and 5.6, we obtain a *fractional* multicut for pairs S in graph G , having cost $O(1) \cdot \Phi^* + O(\log^{1+\epsilon} n) \cdot T^*$. Since the Garg et al. [18] algorithm for multicut is an $O(\log n)$ -approximation relative to the LP, we obtain Theorem 5.2.

From Claim 5.1 and Theorem 5.2, it follows that this algorithm is $O(\log n, \log^{2+\epsilon} n, \beta)$ -discriminating for k -robust multicut. Since $\beta = O(\log^2 n / \log \log n)$, using Lemma 2.2, we obtain an approximation ratio of:

$$\max \left\{ \log n, \frac{\log^2 n}{\log \log n} + \frac{\log^{2+\epsilon} n}{\lambda} \right\}.$$

This is an $O\left(\frac{\log^2 n}{\log \log n}\right)$ -approximation when $\lambda \geq \log^{2\epsilon} n$. On the other hand, when $\lambda \leq \log^{2\epsilon} n$, we can use the trivial algorithm of buying all edges in the second stage (using the GUY algorithm [18]); this implies an $O(\log^{1+2\epsilon} n)$ -approximation. Since $\log^{1+2\epsilon} n = o\left(\frac{\log^2 n}{\log \log n}\right)$, we obtain:

Theorem 5.9 *There is an $O\left(\frac{\log^2 n}{\log \log n}\right)$ -approximation algorithm for k -robust multicut.*

The k -max-min Multicut Problem. The above ideas also lead to a $(c_1 \cdot \log n, c_2 \cdot \log^2 n, c_3 \cdot \log^2 n)$ strongly discriminating algorithm for multicut, where c_1, c_2, c_3 are large enough constants. The algorithm is exactly Algorithm 5 with parameter $\beta := \Theta(\log n) \cdot \rho$ with an appropriate constant factor; recall that $\rho = O(\log n)$ is the approximation ratio for oblivious routing [30]. Lemma 5.6 shows that this algorithm is $(c_1 \cdot \log n, c_2 \cdot \log^2 n, c_3 \cdot \log^2 n)$

discriminating (the parameters are only slightly different and the analysis still applies). To establish the property in Definition 2.3, consider the case $\lambda = 1$ (i.e. $\Phi^* = 0$) and $c(\Phi_T) \geq (c_2 \log^2 n) \cdot T$. Since the [18] algorithm is $O(\log n)$ -approximate relative to the LP, this implies a feasible multicommodity flow on pairs W (since $\Phi^* = 0$ we also have $W = S$) of value at least $(c_4 \log n) \cdot T$ for some constant c_4 . Then the randomized rounding (with oblivious routing) can be used to produce a k -set $W' \subseteq W$ and a feasible multicommodity flow on W' of value at least T ; by weak duality it follows that the minimum multicut on W' is at least T and so Definition 2.3 holds. Thus by Lemma 2.4 we get a randomized $O(\log^2 n)$ -approximation algorithm for k -max-min multicut.

All-or-Nothing Multicommodity Flow. As a possible use of the oblivious routing and randomized-rounding based approach, let us state a result for the all-or-nothing multicommodity flow problem studied by Chekuri et al. [8]: given a capacitated undirected graph $G = (V, E)$ and source-sink pairs $\{s_i, t_i\}$ with demands d_i such that the min-cut(s_i, t_i) = $\Omega(\log^2 n)d_i$, one can approximate the maximum throughput to within an $O(\log n)$ factor without violating the edge-capacities, even with $d_{\max} \geq c_{\min}$ —the results of Chekuri et al. [8, 9] violated the edge-capacities in this case by an additive $d_{\max}$. This capacity violation in the previous all-or-nothing results is precisely the reason they can not be directly used in our analysis of k -robust multicut.

Summarizing Properties from Dual Rounding. The proofs for all problems considered so far (set cover, minimum cut, multicut) used certain dual rounding arguments. We now summarize the resulting properties in a self-contained form.

Theorem 5.10 *Consider any instance of set cover; let $B \in \mathbb{R}_+$ and $k \in \mathbb{Z}_+$ be values such that*

- *the set of minimum cost covering any element costs at least $36 \ln m \cdot \frac{B}{k}$, and*
- *the minimum cost of covering any k -subset of elements is at most B .*

*Then the minimum cost of covering **all** elements is at most $O(\log n) \cdot B$.*

Theorem 5.11 *Consider any instance of minimum cut in an n -vertex undirected graph with root r and terminals X ; let $B \in \mathbb{R}_+$ and $k \in \mathbb{Z}_+$ be values such that*

- *the minimum cut separating r and u costs at least $10 \cdot \frac{B}{k}$, for each terminal $u \in X$.*
- *the minimum cut separating r and S costs at most B , for every k -set $S \in \binom{X}{k}$.*

Then the minimum cut separating r and all terminals X costs at most $O(1) \cdot B$.

Theorem 5.12 *Consider any instance of multicut in an n -vertex undirected graph with source-sink pairs $\{s_i, t_i\}_{i \in [m]}$; let $B \in \mathbb{R}_+$ and $k \in \mathbb{Z}_+$ be values such that*

- *the minimum $s_i - t_i$ cut costs at least $c \cdot \log^2 n \cdot \frac{B}{k}$, for each pair $i \in [m]$.*
- *the minimum multicut separating pairs in P costs at most B , for every k -set $P \in \binom{[m]}{k}$.*

Then the minimum multicut separating all pairs $[m]$ costs at most $O(\log^2 n) \cdot B$. Here c is a universal constant that is independent of the multicut instance.

Such properties rely crucially on the specific problem structure, and cannot hold for general covering problems—even for the Steiner-tree cost function on a tree metric (which, in fact, is submodular). Consider a tree on vertices $\{r, u\} \cup \{v_i\}_{i=1}^n$ with root r and terminals $\{v_i\}_{i=1}^n$. The edges set contains (r, u) with cost k , and for each $i \in [n]$ the edge (u, v_i) with cost one. For parameter $B = 2k$, the cost for connecting any single terminal to the root is $k + 1 > \frac{B}{2}$, whereas the cost for connecting any k -set of terminals is $2k = B$. If a theorem like the ones above held, we might have hoped the cost to connect all the n terminals would be $\tilde{O}(B)$; instead it is $n + k > \frac{n}{2k} \cdot B$. This is also the reason why the algorithms for Steiner tree and Steiner forest (which appear in the next section) are slightly more involved, and their proofs rely on a primal-dual argument instead of dual rounding.

6 k -Robust Steiner Forest

In k -robust Steiner forest, we have a graph $G = (V, E)$ with edge costs $c : E \rightarrow \mathbb{R}_+$, and a set $U \subseteq V \times V$ of potential terminal pairs; any set in $\binom{U}{k}$ is a valid scenario in the second stage. For a set of pairs $S \subseteq V \times V$, the graph G/S is obtained by identifying each pair in S together; $d_{G/S}(\cdot, \cdot)$ is the distance in this “shrunk” graph. The algorithm is given below. This algorithm is a bit more involved than the previous ones, despite a similar general structure: we maintain a set of “fake” pairs S_f that may not belong to U for this case. The following analysis shows a constant-factor guarantee. (Without lines 6-7, the algorithm is more natural, but for that we can currently only show an $O(\log n)$ -approximation; it seems that an $O(1)$ -approximation for that version would imply an $O(\log n)$ -competitiveness for online greedy Steiner forest.)

Algorithm 4 Algorithm for k -Robust Steiner Forest

- 1: **input:** k -robust Steiner forest instance and threshold T .
 - 2: **let** $\beta \leftarrow \Theta(1), \gamma \leftarrow \Theta(1)$ such that $\gamma \leq \beta/2$.
 - 3: **let** $S_r, S_f, W \leftarrow \emptyset$
 - 4: **while** there exists a pair $(s, t) \in U$ with $d_{G/(S_r \cup S_f)}(s, t) > \beta \cdot \frac{T}{k}$ **do**
 - 5: **let** $S_r \leftarrow S_r \cup \{(s, t)\}$
 - 6: **if** $d_G(s, w) < \gamma \cdot \frac{T}{k}$ for some $w \in W$ **then** $S_f \leftarrow S_f \cup \{(s, w)\}$ **else** $W \leftarrow W \cup \{s\}$
 - 7: **if** $d_G(t, w') < \gamma \cdot \frac{T}{k}$ for some $w' \in W$ **then** $S_f \leftarrow S_f \cup \{(t, w')\}$ **else** $W \leftarrow W \cup \{t\}$
 - 8: **end while**
 - 9: **output** first stage solution Φ_T to be the 2-approximate Steiner forest [1, 19] on pairs S_r along with shortest-paths connecting every pair in S_f .
 - 10: **define** $\text{Augment}_T(\{i\})$ to be the edges on the $s_i - t_i$ shortest-path in $G/(S_r \cup S_f)$, for each pair $i \in U$.
 - 11: **output** second stage solution Augment_T where $\text{Augment}_T(S) := \bigcup_{i \in D} \text{Augment}_T(\{i\})$ for all $D \subseteq U$.
-

Claim 6.1 (Property A for Steiner forest) *For all $T \geq 0$ and $D \in \binom{U}{k}$, the edges $\Phi_T \cup \text{Augment}_T(D)$ connect every pair in D , and have cost $c(\text{Augment}_T(D)) \leq \beta T$.*

Proof: The first part is immediate from the definition of Augment_T and the fact that Φ_T connects every pair in $S_r \cup S_f$. The second part follows from the termination condition $d_{G/(S_r \cup S_f)}(s_i, t_i) \leq \beta \cdot \frac{T}{k}$ for all pairs $i \in U$; this implies $c(\text{Augment}_T(D)) \leq \sum_{i \in D} c(\text{Augment}_T(\{i\})) \leq \sum_{i \in D} d_{G/(S_r \cup S_f)}(s_i, t_i) \leq \frac{|D|}{k} \cdot \beta T$. ■

Lemma 6.2 *The optimal value of the Steiner forest on pairs S_r is at least $|W| \times \frac{\gamma T}{2k}$.*

Proof: Consider the primal (covering) and dual (packing) LPs corresponding to Steiner forest on S_r . Note that for each pair $i \in S_r$, the distance $d_G(s_i, t_i) \geq \beta \cdot \frac{T}{k} \geq 2\gamma \cdot \frac{T}{k}$; so any ball of radius $\frac{\gamma}{2} \cdot \frac{T}{k}$ around a vertex in S_r may be used in the dual packing problem since it separates some pair in S_r . Observe that W consists of only vertices from S_r , and each time we add a vertex to W , it is at least $\gamma T/k$ distant from any other vertex in W . Hence we can feasibly pack dual balls of radius $\frac{\gamma}{2} \cdot \frac{T}{k}$ around each W -vertex. This is a feasible dual to the Steiner forest instance on S_r , of value $|W| \gamma / 2 \cdot T/k$. The lemma now follows by weak duality. ■

Lemma 6.3 *The number of “witnesses” $|W|$ is at least the number of “real” pairs $|S_r|$, and $|S_r|$ is at least the number of “fake” pairs $|S_f|$.*

Proof: Partition the set S_r as follows: S_g are the pairs where both end-points are added to W , S_o are the pairs where exactly one end-point is added to W , and S_b are the pairs where neither end-point is added to W . It follows that $|S_r| = |S_g| + |S_o| + |S_b|$ and $|W| = 2 \cdot |S_g| + |S_o|$.

Consider an auxiliary graph $H = (W, E(W))$ on the vertex set W which is constructed incrementally:

- When a pair $(s, t) \in S_g$ is added, vertices s, t are added to W , and edge (s, t) is added to $E(W)$.
- Suppose a pair $(s, t) \in S_o$ is added, where s is added to W , but t is not because it is “blocked” by $w' \in W$. In this case, vertex s is added, and edge (s, w') is added to $E(W)$.

- Suppose a pair $(s, t) \in S_b$ is added, where s and t are “blocked” by w and w' respectively. In this case, no vertex is added, but an edge (w, w') is added to $E(W)$.

Claim 6.4 *At any point in the algorithm if $x, y \in W$ lie in the same component of H then $d_{G/(S_f \cup S_r)}(x, y) = 0$.*

Proof: By induction on the algorithm, and the construction of the graph H .

- Suppose pair $(s, t) \in S_g$ is added, then the claim is immediate. H has one new connected component $\{s, t\}$ and others are unchanged. Since $(s, t) \in S_r$, $d_{G/(S_f \cup S_r)}(s, t) = 0$ and the invariant holds.
- Suppose pair $(s, t) \in S_o$ is added, with s added to W and t blocked by $w' \in W$. In this case, the component of H containing w' grows to also contain s ; other components are unchanged. Furthermore (t, w') is added to S_f and (s, t) to S_r , which implies $d_{G/(S_f \cup S_r)}(s, w') = 0$. So the invariant continues to hold.
- Suppose pair $(s, t) \in S_b$ is added, with s and t blocked by $w, w' \in W$ respectively. In this case, the components containing w and w' get merged; others are unchanged. Also $(s, w), (t, w')$ are added to S_f and (s, t) to S_r ; so $d_{G/(S_f \cup S_r)}(w, w') = 0$, and the invariant continues to hold.

Since these are the only three cases, this proves the claim. $\blacksquare$

Claim 6.5 *The auxiliary graph H does not contain a cycle when $\gamma \leq \beta/2$*

Proof: For a contradiction, consider the first edge (x, y) that when added to H by the process above creates a cycle. Let (s, t) be the pair that caused this edge to be added, and consider the situation just before (s, t) is added to S_r . Since (x, y) causes a cycle, x, y belong to the same component of H , and hence $d_{G/(S_f \cup S_r)}(x, y) = 0$ by the claim above. But since x is either s or its “blocker” w , and y is either t or its blocker w' , it follows that $d_{G/(S_f \cup S_r)}(s, t) < 2\gamma \cdot \frac{T}{k} \leq \beta \cdot \frac{T}{k}$. But this contradicts the condition which would cause (s, t) to be chosen into S_r by the algorithm. $\blacksquare$

Now for some counting. Consider graph H at the end of the algorithm: W denotes its vertices, and E its edges. From the construction of H , we obtain $|W| = 2 \cdot |S_g| + |S_o|$ and $|E| = |S_g| + |S_o| + |S_b| = |S_r|$. Since H is acyclic, $|S_r| = |E| \leq |W| - 1$. Also note that $|S_f| = 2 \cdot |S_b| + |S_o| = 2 \cdot |S_r| - |W| < |S_r|$. Thus we have $|W| \geq |S_r| \geq |S_f|$ as required in the lemma. $\blacksquare$

Theorem 6.6 (Property B for Steiner forest) *Let Φ^* denote the optimal first stage solution (and its cost), and T^* the optimal second stage cost. If $T \geq T^*$ then $c(\Phi_T) \leq \frac{4\gamma}{\gamma-2} \cdot (\Phi^* + T^*)$.*

Proof: Let $|S_r| = \alpha k$. Using Lemma 6.3, Lemma 6.2 and the optimal solution,

$$\frac{\gamma}{2} \cdot \alpha \cdot T \leq |W| \cdot \frac{\gamma T}{2k} \leq OPT(S_r) \leq \Phi^* + \left\lceil \frac{|S_r|}{k} \right\rceil T^* \leq \Phi^* + T^* + \alpha \cdot T^* \leq \Phi^* + T^* + \alpha T \quad (6.2)$$

Thus $\alpha \cdot T \leq \frac{2}{\gamma-2} \cdot (\Phi^* + T^*)$ and $OPT(S_r) \leq \frac{\gamma}{\gamma-2} \cdot (\Phi^* + T^*)$. So the 2-approximate Steiner forest on S_r has cost at most $\frac{2\gamma}{\gamma-2} \cdot (\Phi^* + T^*)$. Note that the distance between each pair in S_f is at most $\gamma \cdot \frac{T}{k}$; so the total length of shortest-paths in S_f is at most $|S_f| \cdot \gamma \cdot \frac{T}{k} \leq |S_r| \cdot \gamma \cdot \frac{T}{k}$ (again by Lemma 6.3). Thus the algorithm’s first-stage cost is at most $\frac{2\gamma}{\gamma-2} \cdot (\Phi^* + T^*) + \alpha\gamma \cdot T \leq \frac{4\gamma}{\gamma-2} \cdot (\Phi^* + T^*)$. $\blacksquare$

Theorem 6.7 (Steiner Forest Main Theorem) *There is a 10-approximation for k -robust Steiner forest.*

Proof: Using Claim 6.1 and Theorem 6.6, we obtain a $(\frac{4\gamma}{\gamma-2}, \frac{4\gamma}{\gamma-2}, \beta)$ -discriminating algorithm (Definition 2.1) for k -robust Steiner forest. Setting $\beta = 2\gamma$ and $\gamma := 2 + 2 \cdot (1 - 1/\lambda)$, Lemma 2.2 implies an approximation ratio of $\max\{\frac{4\gamma}{\gamma-2}, \frac{4\gamma/\lambda}{\gamma-2} + 2\gamma\} \leq 4 + \frac{4}{1-1/\lambda}$. Again the trivial algorithm that only buys edges in the second-stage achieves a 2λ -approximation. Taking the better of the two, the approximation ratio is $\min\{2\lambda, 4 + \frac{4}{1-1/\lambda}\} < 10$. $\blacksquare$

The k -max-min Steiner Forest Problem. We now extend the k -robust Steiner forest algorithm to be $(\frac{4\gamma}{\gamma-2}, \frac{4\gamma}{\gamma-2}, 2\gamma)$ strongly discriminating (when $\gamma = 3$). As shown earlier, it is indeed discriminating. To show that Definition 2.3 holds, consider the proof of Theorem 6.6 when $\lambda = 1$ (so $\Phi^* = 0$) and suppose $c(\Phi_T) \geq \frac{4\gamma}{\gamma-2}T \geq 2\gamma T$. The algorithm to output the k -set Q has two cases.

1. If the number of “real” pairs $|S_r| \leq k$ then $Q := S_r$. We have:

$$c(\Phi_T) \leq 2 \cdot \text{OPT}(S_r) + \frac{\gamma T}{k} |S_f| \leq 2 \cdot \text{OPT}(S_r) + \frac{\gamma T}{k} |S_r| \leq 2 \cdot \text{OPT}(S_r) + \gamma T.$$

The first inequality is by definition of Φ_T and since distance between each pair in S_f is at most $\gamma \cdot \frac{T}{k}$, the second inequality is by Lemma 6.3, and the last inequality uses $|S_r| \leq k$. Since $c(\Phi_T) \geq 2\gamma T$, it follows that $\text{OPT}(S_r) \geq \gamma T/2 \geq T$.

2. If $|S_r| > k$ then the number of “witnesses” $|W| \geq |S_r| > k$, by Lemma 6.3. Let $Q \subseteq S_r$ be any k -set of pairs such that for each $i \in Q$ at least one of $\{s_i, t_i\}$ is in W . By the construction of S_r , we can feasibly pack dual balls of radius $\frac{\gamma T}{2k}$ around each W -vertex, and so $\text{OPT}(Q) \geq |Q| \cdot \frac{\gamma T}{2k} = \frac{\gamma T}{2} \geq T$.

Thus we obtain a constant-factor approximation algorithm for k -max-min Steiner forest.

7 Final Remarks

In this paper, we presented a unified approach to directly solving k -robust covering problems and k -max-min problems. The results for all problems except multicut are fairly tight (and nearly match the best-possible for the offline versions). It would be interesting to obtain an $O(\log n)$ -approximation for k -robust and k -max-min multicut.

As mentioned earlier, approximating the *value* of any max-min problem reduces to the corresponding robust problem, for *any* uncertainty set. We show in the companion paper [23] that there is also a relation in the reverse direction—for any covering problem that admits good offline and online approximation algorithms, an algorithm for the max-min problem implies one for the robust version. This reduction can be used to give algorithms for robust covering under matroid- and knapsack-type uncertainty sets [23].

Acknowledgments. We thank Chandra Chekuri, Ravishankar Krishnaswamy, Danny Segev, and Maxim Sviridenko for invaluable discussions.

References

- [1] Ajit Agrawal, Philip Klein, and R. Ravi. When trees collide : An approximation algorithm for the generalized Steiner problem on networks. *SIAM Journal on Computing*, 24(3):445–456, 1995.
- [2] Shipra Agrawal, Yichuan Ding, Amin Saberi, and Yinyu Ye. Correlation Robust Stochastic Optimization. <http://arxiv.org/abs/0902.1792>, 2009.
- [3] Noga Alon, Baruch Awerbuch, Yossi Azar, Niv Buchbinder, and Seffi Naor. The Online Set Cover Problem. In *STOC*, pages 100–105, 2003.
- [4] Noga Alon, Baruch Awerbuch, Yossi Azar, Niv Buchbinder, and Seffi Naor. A General Approach to Online Network Optimization Problems. In *SODA*, pages 570–579, 2004.
- [5] Piotr Berman and Chris Coulston. On-line algorithms for Steiner tree problems. In *STOC*, pages 344–353, 1997.

- [6] Jaroslaw Byrka, Fabrizio Grandoni, Thomas Rothvoß, and Laura Sanità. An improved lp-based approximation for steiner tree. In *STOC '10: Proceedings of the 42nd ACM symposium on Theory of computing*, pages 583–592, 2010.
- [7] G. Calinescu, C. Chekuri, M. Pál, and J. Vondrák. Maximizing a monotone submodular function under a matroid constraint. *SIAM J. Computing (Preliminary version IPCO 2007)*, To appear.
- [8] Chandra Chekuri, Sanjeev Khanna, and F. Bruce Shepherd. The all-or-nothing multicommodity flow problem. In *STOC '04: Proceedings of the thirty-sixth annual ACM symposium on Theory of computing*, pages 156–165, 2004.
- [9] Chandra Chekuri, Sanjeev Khanna, and F. Bruce Shepherd. Multicommodity flow, well-linked terminals, and routing problems. In *STOC '05: Proceedings of the thirty-seventh annual ACM symposium on Theory of computing*, pages 183–192, 2005.
- [10] W.J. Cook, W.H. Cunningham, W.R. Pulleyblank, and A. Schrijver. *Combinatorial Optimization*. John Wiley and Sons, 1998.
- [11] Kedar Dhamdhere, Vineet Goyal, R. Ravi, and Mohit Singh. How to pay, come what may: Approximation algorithms for demand-robust covering problems. In *FOCS*, pages 367–378, 2005.
- [12] Jittat Fakcharoenphol, Satish Rao, and Kunal Talwar. A tight bound on approximating arbitrary metrics by tree metrics. *J. Comput. System Sci.*, 69(3):485–497, 2004.
- [13] Uriel Feige. A threshold of $\ln n$ for approximating set cover. *J. ACM*, 45(4):634–652, 1998.
- [14] Uriel Feige, Kamal Jain, Mohammad Mahdian, and Vahab S. Mirrokni. Robust combinatorial optimization with exponential scenarios. In *IPCO*, volume 4513 of *Lecture Notes in Computer Science*, pages 439–453, 2007.
- [15] M. L. Fisher, G. L. Nemhauser, and L. A. Wolsey. An analysis of approximations for maximizing submodular set functions II. *Mathematical Programming Study*, 8:73–87, 1978.
- [16] Rajiv Gandhi, Samir Khuller, and Aravind Srinivasan. Approximation algorithms for partial covering problems. *J. Algorithms*, 53(1):55–84, 2004.
- [17] Naveen Garg. Saving an epsilon: a 2-approximation for the k-mst problem in graphs. In *STOC '05: Proceedings of the thirty-seventh annual ACM symposium on Theory of computing*, pages 396–402, 2005.
- [18] Naveen Garg, Vijay V. Vazirani, and Mihalis Yannakakis. Approximate Max-Flow Min-(Multi)Cut Theorems and Their Applications. *SIAM J. Comput.*, 25(2):235–251, 1996.
- [19] Michel X. Goemans and David P. Williamson. A General Approximation Technique for Constrained Forest Problems. *SIAM J. Comput.*, 24(2):296–317, 1995.
- [20] Daniel Golovin, Vineet Goyal, and R. Ravi. Pay today for a rainy day: improved approximation algorithms for demand-robust min-cut and shortest path problems. In *STACS 2006*, volume 3884 of *Lecture Notes in Comput. Sci.*, pages 206–217. Springer, Berlin, 2006.
- [21] Daniel Golovin, Viswanath Nagarajan, and Mohit Singh. Approximating the k-multicut problem. In *SODA '06: Proceedings of the seventeenth annual ACM-SIAM symposium on Discrete algorithm*, pages 621–630, 2006.
- [22] A. Gupta, M. T. Hajiaghayi, V. Nagarajan, and R. Ravi. Dial a ride from k-forest. In *Proceedings of the 15th Annual European Symposium on Algorithms*, pages 241–252, 2007.

- [23] Anupam Gupta, Viswanath Nagarajan, and R. Ravi. Robust and MaxMin Optimization under Matroid and Knapsack Uncertainty Sets. *arXiv*, 2010.
- [24] Chris Harrelson, Kirsten Hildrum, and Satish Rao. A polynomial-time tree decomposition to minimize congestion. In *SPAA*, pages 34–43, 2003.
- [25] M. Imase and B.M. Waxman. Dynamic Steiner tree problem. *SIAM J. on Discrete Mathematics*, 4(3):369–384, 1991.
- [26] Nicole Immorlica, David Karger, Maria Minkoff, and Vahab S. Mirrokni. On the costs and benefits of procrastination: approximation algorithms for stochastic combinatorial optimization problems. In *SODA*, pages 691–700, 2004.
- [27] Rohit Khandekar, Guy Kortsarz, Vahab S. Mirrokni, and Mohammad R. Salavatipour. Two-stage robust network design with exponential scenarios. In *ESA*, volume 5193 of *Lecture Notes in Computer Science*, pages 589–600, 2008.
- [28] R. Motwani and P. Raghavan. *Randomized Algorithms*. Cambridge University Press, 1995.
- [29] G. L. Nemhauser, L. A. Wolsey, and M. L. Fisher. An analysis of approximations for maximizing submodular set functions I. *Mathematical Programming*, 14:265–294, 1978.
- [30] Harald Räcke. Optimal hierarchical decompositions for congestion minimization in networks. In *STOC*, pages 255–264, 2008.
- [31] R. Ravi and A. Sinha. Hedging uncertainty: approximation algorithms for stochastic optimization problems. In *IPCO*, pages 101–115, 2004.
- [32] A. Schrijver. *Combinatorial Optimization*. Springer, 2003.
- [33] D. Shmoys and C. Swamy. Stochastic Optimization is (almost) as Easy as Deterministic Optimization. In *FOCS*, pages 228–237, 2004.
- [34] Petr Slavík. Improved performance of the greedy algorithm for partial cover. *Inf. Process. Lett.*, 64(5):251–254, 1997.
- [35] M. Sviridenko. A note on maximizing a submodular set function subject to knapsack constraint. *Operations Research Letters*, 32:41–43, 2004.
- [36] C. Swamy. Algorithms for Probabilistically-Constrained Models of Risk-Averse Stochastic Optimization with Black-Box Distributions. <http://arxiv.org/abs/0805.0389>, 2008.
- [37] J. Vondrák. Optimal approximation for the submodular welfare problem in the value oracle model. In *STOC*, pages 67–74, 2008.

A k -Robust Steiner Tree

In the k -robust Steiner tree, we are given a graph $G = (V, E)$ with edge costs $c : E \rightarrow \mathbb{R}_+$, a root vertex r , and a set $U \subseteq V$ of potential terminals. Any set of k terminals from U —i.e., any set in $\binom{U}{k}$ —is a valid scenario in the second stage. Let $d(\cdot, \cdot)$ be the shortest-path distance according to the edge costs. For a set $S \subseteq V$ of terminals, define the distance $d(v, S) := \min_{w \in S} d(v, w)$.

By the results in Section 2.1, a discriminating algorithm for this problem immediately gives us an algorithm for the robust version, and this is how we shall proceed. Here is our discriminating algorithm for k -robust Steiner tree: it picks a $\beta T/k$ -net S of the terminals in U , and builds a MST on S as the first stage.

Algorithm 5 Algorithm for k -Robust Steiner Tree

- 1: **input:** instance of k -robust Steiner tree and threshold T .
 - 2: **let** $\beta \leftarrow \Theta(1)$, $S \leftarrow \{r\}$.
 - 3: **while** there exists a terminal $v \in U$ with $d(v, S) > \beta \cdot \frac{T}{k}$ **do**
 - 4: $S \leftarrow S \cup \{v\}$
 - 5: **end while**
 - 6: **output** first-stage solution Φ_T to be a minimum spanning tree on S .
 - 7: **for each** $i \in U$, define $\text{Augment}_T(\{i\})$ to be the edges on a shortest-path from i to S .
 - 8: **output** second-stage solution Augment_T where $\text{Augment}_T(D) := \bigcup_{i \in D} \text{Augment}_T(\{i\})$ for all $D \subseteq U$.
-

To show that the algorithm is discriminating, we need to show the two properties in Definition 2.1. The first property is almost immediate from the construction: since every point in $U \setminus S$ is close to some point in the net S , this automatically ensures that the second stage recourse cost is small.

Claim A.1 (Property A for Steiner Tree) *For all $T \geq 0$ and $D \in \binom{U}{k}$, the edges $\Phi_T \cup \text{Augment}_T(D)$ connect the terminals in D to the root r , and have cost $c(\text{Augment}_T(D)) \leq \beta T$.*

Proof: From the definition of the second-stage solution, $\text{Augment}_T(D)$ contains the edges on shortest paths from each D -vertex to the set S . Moreover, Φ_T is a minimum spanning tree on S (which in turn contains the root r). Hence $\Phi_T \cup \text{Augment}_T(D)$ connects D to the root r . To bound the cost, note that by the termination condition in the **while** loop, every terminal $i \in U$ satisfies $d(i, S) \leq \beta \frac{T}{k}$. Thus,

$$c(\text{Augment}_T(D)) \leq \sum_{i \in D} c(\text{Augment}_T(\{i\})) = \sum_{i \in D} d(i, S) \leq \frac{|D|}{k} \cdot \beta T.$$

This completes the proof that the algorithm above satisfies Property A. ■

It now remains to show that the algorithm satisfies Property B as well. Let us show this for a sub-optimal settings of values; we will improve on these values subsequently. The proof is dual-based and shows that if the cost of the MST on S were large, then the optimal first stage solution cost Φ^* must have been large as well!

Theorem A.2 (Property B for Steiner tree) *Let Φ^* denote the optimal first stage solution (and its cost), and T^* the optimal second stage cost. If $T > T^*$ then the first stage cost $c(\Phi_T) \leq 2 \cdot \frac{\beta}{\beta-2} \cdot (\Phi^* + T^*)$.*

Proof: Suppose $|S| = \alpha k$. We can divide up S into $\lceil \alpha \rceil$ sets $S_1, S_2, \dots, S_{\lceil \alpha \rceil}$ with at most k terminals each, and let $E(S_i)$ denote the second-stage edges bought by the optimal solution under scenario S_i . Hence $\Phi^* \cup (\bigcup_{i \leq \lceil \alpha \rceil} E(S_i))$ is a feasible solution to the Steiner tree on S of cost at most $\Phi^* + \lceil \alpha \rceil \cdot T^*$. Also, since each of the points in S is at least at distance $\beta T/k$ from each other, we get (below $OPT(S)$ is the length of the minimum Steiner tree on S),

$$\frac{\beta}{2} \cdot \alpha T = |S| \cdot \frac{\beta}{2} \cdot \frac{T}{k} \leq OPT(S) \leq \Phi^* + \lceil \alpha \rceil \cdot T^* \leq \Phi^* + (\alpha + 1) \cdot T^* \leq \Phi^* + T^* + \alpha T.$$

Hence $\alpha T \leq \frac{2}{\beta-2}(\Phi^* + T^*)$ and $OPT(S) \leq \frac{\beta}{\beta-2} \cdot (\Phi^* + T^*)$; since the MST heuristic is a 2-approximation to the optimal Steiner tree, we get the theorem. ■

Combining Claim A.1 and Theorem A.2 shows that our algorithm is a $(\frac{2\beta}{\beta-2}, \frac{2\beta}{\beta-2}, \beta)$ -discriminating algorithm for k -robust Steiner tree. Setting, say, $\beta = 4$ and applying Lemma 2.2 gives us an $\max(4, 4 + 4) = 8$ -approximation for k -robust Steiner tree. In the next subsection, we will show how to improve this guarantee.

A.1 Improved Approximation for Steiner Tree

In the previous analysis, we just wanted to show the main ideas and hence were somewhat sloppy with the analysis. Let us now show how to get a tighter bound using a fractional analysis.

Theorem A.3 (Improved Property B for Steiner Tree) *If $T \geq T^*$ then $c(\Phi_T) \leq \frac{2\beta}{\beta-2} \cdot \Phi^* + 2 \cdot T^*$.*

Proof: Firstly suppose $|S| \leq k$: then it is clear that there is a Steiner tree on $\{r\} \cup S$ of cost at most $\Phi^* + T^*$, and the algorithm finds one of cost at most twice that. In the following assume that $|S| > k$.

Let $LP(S)$ denote the minimum length of a *fractional* Steiner tree on terminals $\{r\} \cup S$. Since each of the points in S is at least at distance $\beta \cdot \frac{T}{k} \geq \beta \cdot \frac{T^*}{k}$ from each other, we get $LP(S) \geq \frac{\beta}{2k} \cdot |S| \cdot T^*$. We now construct a fractional Steiner tree $x : E \rightarrow \mathbb{R}_+$ of small length. Number the terminals in S arbitrarily, and for each $1 \leq j \leq |S|$ let $A_j = \{j, j+1, \dots, j+k-1\}$ (modulo $|S|$). Let $\Pi_j \subseteq E \setminus \Phi^*$ denote the second-stage edges bought in the optimal solution under scenario A_j : so $\Phi^* \cup \Pi_j$ is a Steiner tree on terminals $\{r\} \cup A_j$, and $c(\Pi_j) \leq T^*$. Define $x := \chi(\Phi^*) + \frac{1}{k} \cdot \sum_{j=1}^{|S|} \chi(\Pi_j)$. We claim that x supports unit flow from r to any $i \in S$: note that there are k sets $A_{i-k+1}, \dots, A_i$ that contain i , and for each $i-k+1 \leq j \leq i$, we have $\frac{1}{k} \cdot (\chi(\Phi^*) + \chi(\Pi_j))$ supports $\frac{1}{k}$ flow from r to i . Thus x is a feasible fractional Steiner tree on $\{r\} \cup S$, of cost at most $\Phi^* + \frac{|S|}{k} \cdot T^*$. Combined with the lower bound on $LP(S)$,

$$|S| \cdot \frac{\beta}{2} \cdot \frac{T^*}{k} \leq LP(S) \leq \Phi^* + \frac{|S|}{k} \cdot T^*. \quad (\text{A.3})$$

Thus we have $LP(S) \leq \frac{\beta}{\beta-2} \cdot \Phi^*$, which implies the theorem since the minimum spanning tree on $\{r\} \cup S$ costs at most twice $LP(S)$. $\blacksquare$

From Claim A.1 and Theorem A.3, we now get that the algorithm is $(\frac{2\beta}{\beta-2}, 2, \beta)$ -discriminating. Thus, setting $\beta = 2 - \frac{1}{\lambda} + \sqrt{4 + 1/\lambda^2}$ and applying Lemma 2.2, we get the following approximation ratio.

$$\max \left\{ \frac{2\beta}{\beta-2}, \frac{2}{\lambda} + \beta \right\} = 2 + \frac{1}{\lambda} + \sqrt{4 + \frac{1}{\lambda^2}}.$$

On the other hand, the trivial algorithm which does nothing in the first stage is a $1.55 \cdot \lambda$ approximation. Hence the better of these two ratios gives an approximation bound better than 4.5.

The k -max-min Steiner Tree Problem. We show that the above algorithm can be extended to be $(\frac{2\beta}{\beta-2}, 2, \beta)$ strongly discriminating. As shown above, it is indeed discriminating. To show that Definition 2.3 holds, consider the proof of Theorem A.3 when $\lambda = 1$ (so $\Phi^* = 0$) and suppose that $c(\Phi_T) \geq 2T$. The algorithm to output the k -set Q proceeds via two cases.

1. If $|S| \leq k$ then $Q := S$. The minimum Steiner tree on Q is at least half its MST, i.e. at least $\frac{1}{2}c(\Phi_T) \geq T$.
2. If $|S| > k$ then $Q \subseteq S$ is *any* k -set; by the construction of S , we can feasibly pack dual balls of radius $\beta \frac{T}{k}$ around each Q -vertex, and so $LP(Q) \geq \beta T \geq T$. Thus the minimum Steiner tree on Q is at least T .

A.2 Unrooted Steiner tree

We note that the k -robust Steiner tree problem studied above differs from [27] since there is no root in the model of [27]. In the unrooted version, any subset of k terminals appear in the second stage, and the goal is to connect them *amongst each other*. We show that a small modification in the proof implies that Algorithm 1 (where $r \in U$ is set to an arbitrary terminal) achieves a good approximation in the unrooted case as well. This algorithm is essentially same as the one used by [27], but with different parameters: hence our framework can be viewed as generalizing their algorithm. Our proof is somewhat shorter and gives a slightly better approximation ratio.

Below, Φ^* and T^* denote the optimal first and second stage costs for the given unrooted instance. It is clear that Claim A.1 continues to hold in this case as well: hence Property A of Definition 2.1 is satisfied. We next bound the first stage cost of the algorithm (i.e. Property B of Definition 2.1).

Theorem A.4 (Property B for Unrooted Steiner Tree) *If $T \geq T^*$ then $c(\Phi_T) \leq \frac{2\beta}{\beta-2} \cdot \Phi^* + 2T^*$.*

Proof: Firstly suppose $|S| \leq k$: then it is clear that there is a Steiner tree on S of cost at most $\Phi^* + T^*$, and the algorithm finds one of cost at most twice that. In the following assume that $|S| > k$.

Let $LP(S)$ denote the minimum length of a *fractional* Steiner tree on terminals S (recall, no root here). Since each of the points in S is at least at distance $\beta \cdot \frac{T^*}{k} \geq \beta \cdot \frac{T^*}{2k}$ from each other, we get $LP(S) \geq \frac{\beta}{2k} \cdot |S| \cdot T^*$. We now construct a fractional Steiner tree $x : E \rightarrow \mathbb{R}_+$ of small length. Number the terminals in S arbitrarily, and for each $1 \leq j \leq |S|$ let $A_j = \{j, j+1, \dots, j+k-1\}$ (modulo $|S|$). Let $\Pi_j \subseteq E \setminus \Phi^*$ denote the second-stage edges bought in the optimal solution under scenario A_j : so $\Phi^* \cup \Pi_j$ is a Steiner tree on terminals A_j , and $c(\Pi_j) \leq T^*$. Define $x := \chi(\Phi^*) + \frac{1}{k} \cdot \sum_{j=1}^{|S|} \chi(\Pi_j)$.

Claim A.5 *For any $i \in S$, x supports a unit flow from terminal i to $i+1$ (modulo $|S|$).*

Proof: Note that there are $k-1$ sets $A_{i-k+2}, \dots, A_i$ that contain both i and $i+1$. Let $J := \{i-k+2, \dots, i\}$. So for each $j \in J$, we have $\frac{1}{k} \cdot (\chi(\Phi^*) + \chi(\Pi_j))$ supports $\frac{1}{k}$ flow from i to $i+1$. Furthermore, $(\bigcup_{l \in S \setminus J} \Pi_l) \cup \Phi^*$ is a Steiner tree connecting terminals $\bigcup_{l \in S \setminus J} A_l \supseteq \{i, i+1\}$; i.e. $\frac{1}{k} \cdot \left(\chi(\Phi^*) + \sum_{l \in S \setminus J} \chi(\Pi_l) \right)$ also supports $\frac{1}{k}$ flow from i to $i+1$. Thus we obtain the claim. ■

Thus x is a feasible fractional Steiner tree on terminal S , of cost at most $\Phi^* + \frac{|S|}{k} \cdot T^*$. Combined with the lower bound on $LP(S)$,

$$|S| \cdot \frac{\beta}{2} \cdot \frac{T^*}{k} \leq LP(S) \leq \Phi^* + \frac{|S|}{k} \cdot T^*. \quad (\text{A.4})$$

Thus we have $LP(S) \leq \frac{\beta}{\beta-2} \cdot \Phi^*$, which implies the theorem since the minimum spanning tree on S costs at most twice $LP(S)$. ■

Thus by the same calculation as in the rooted case, we obtain a result that slightly improves on the constants obtained by [27] for the same problem.

Theorem A.6 *There is a 4.5-approximation algorithm for (unrooted) k -robust Steiner tree.*

B k -Robust Set Cover with Non-uniform Inflation

Consider the k -robust set cover problem where there is a set system $(U, \{R_j\}_{j=1}^m)$ with a universe of n elements and m sets with cost-vectors $b, c \in \mathbb{R}_+^m$ (for first and second stage resp.), and a bound k on the cardinality of the realized demand-set. The model considered in Section 3 is the special case when $c = \lambda b$ for some uniform inflation factor λ . Here we consider the general case of *set-dependent inflation*, and show that the same result holds. We may assume WLOG that the first-stage cost for each set is at most its second-stage cost, i.e. $b \leq c$. (If some set R has $c_R < b_R$, then we pretend that its first-stage cost is c_R ; and if R is chosen into the first-stage solution it can be always bought in the second stage).

Under non-uniform inflations, the definition of an $(\alpha_1, \alpha_2, \beta)$ -discriminating algorithm is the same as Definition 2.1 where Condition B is replaced by:

B'. Let Φ^* denote the optimal first stage solution, and T^* the optimal second stage c -cost (hence the optimal value $\text{Opt} = b(\Phi^*) + T^*$). If the threshold $T \geq T^*$ then the first stage cost $b(\Phi_T) \leq \alpha_1 \cdot \Phi^* + \alpha_2 \cdot T^*$.

It can be shown exactly as in Lemma 2.2, that any such algorithm is a $\max\{\alpha_1, \alpha_2 + \beta\}$ -approximation for k -robust set cover. Note that the factor α_2 was scaled down by λ in the uniform inflation case (Lemma 2.2). The algorithm and analysis here are very similar to that for k -robust set-cover under uniform inflation (Section 3).

We will show that this algorithm is $(H_n, 12H_n, 36 \ln m)$ -discriminating. The following claim is immediate.

Claim B.1 (Property A) *For all $T \geq 0$ and $\omega \subseteq U$, the sets $\Phi_T \cup \text{Augment}_T(\omega)$ cover elements ω ; additionally if $|\omega| \leq k$ then the cost $c(\text{Augment}_T(\omega)) \leq \beta T$.*

Theorem B.2 (Property B') *Assume $\beta \geq 36 \cdot \ln m$. If $T \geq T^*$ then $b(\Phi_T) \leq H_n \cdot (b(\Phi^*) + 12 \cdot T^*)$.*

Algorithm 6 Algorithm for Cardinality Robust Set Cover with non-uniform inflation

- 1: **input:** robust set-cover instance and bound T .
 - 2: **let** $\beta \leftarrow 36 \cdot \ln m$, and $S \leftarrow \{v \in U \mid \text{minimum } c\text{-cost set covering } v \text{ has cost at least } \beta \cdot \frac{T}{k}\}$.
 - 3: **output** first stage solution Φ_T as the Greedy-Set-Cover(S) under b -costs.
 - 4: **define** $\text{Augment}_T(\{i\})$ as the minimum c -cost set covering i if $i \in U \setminus S$, and $\emptyset$ otherwise.
 - 5: **output** second stage solution Augment_T where $\text{Augment}_T(\omega) := \bigcup_{i \in \omega} \text{Augment}_T(\{i\})$ for all $\omega \subseteq U$.
-

Proof: We will show that there is a *fractional* solution $\bar{x}$ for covering S with small b -cost, at most $b(\Phi^*) + 12 \cdot T^*$, whence rounding this to an integer solution implies the theorem. For a contradiction, assume not: let every fractional set cover be expensive, and hence there must be a dual solution of large value.

Let $S' \subseteq S$ denote the elements that are *not* covered by the optimal first stage Φ^* , and let $\mathcal{F}' \subseteq \mathcal{F}$ denote the sets that contain at least one element from S' . By the choice of S , all sets in $\mathcal{F}'$ have c -cost at least $\beta \cdot \frac{T}{k} \geq \beta \cdot \frac{T^*}{k}$. Define the “coarse” cost for a set $R \in \mathcal{F}'$ to be $\hat{c}_R = \lceil \frac{c_R}{\beta T^*/k} \rceil$. For each set $R \in \mathcal{F}'$, since $c_R \geq \frac{\beta T^*}{k} \geq \frac{6T^*}{k}$, it follows that $\hat{c}_R \cdot \frac{6T^*}{k} \in [c_R, 2 \cdot c_R)$, and also that $\hat{c}_R \geq \beta/6$.

Now consider the LP for the set cover instance with elements S' and sets $\mathcal{F}'$ having the coarse costs $\hat{c}$. Let $\{x_R\}_{R \in \mathcal{F}'}$ be an optimal fractional solution; then Claim 3.3 applies directly to yield:

$$\sum_{R \in \mathcal{F}'} \hat{c}_R \cdot x_R \leq 2 \cdot k \tag{B.5}$$

Given the primal LP solution $\{x_R\}_{R \in \mathcal{F}'}$ to cover elements in S' , define a fractional solution z covering elements S as follows: define $z_R = 1$ if $R \in \Phi^*$, $z_R = x_R$ if $R \in \mathcal{F}'$, and $z_R = 0$ otherwise. Since the solution z contains Φ^* integrally, it covers elements $S \setminus S'$ (i.e. the portion of S covered by Φ^*); since $z_R \geq x_R$ for all $R \in \mathcal{F}'$, z fractionally covers S' . Finally, the b -cost of this solution is:

$$b \cdot z = b(\Phi^*) + b \cdot x \leq b(\Phi^*) + c \cdot x \leq b(\Phi^*) + \frac{6T^*}{k} \cdot (\hat{c} \cdot x) \leq b(\Phi^*) + 12 \cdot T^*,$$

where the second inequality uses $b \leq c$, the next one is by definition of $\hat{c}$ and the last inequality is from (B.5). Thus we have an LP solution of b -cost $\Phi^* + 12T^*$, and since the greedy algorithm is an H_n -approximation relative to the LP value, this completes the proof. $\blacksquare$

Thus we obtain:

Theorem B.3 *There is an $O(\log m + \log n)$ -approximation for k -robust set cover with set-dependent inflations.*